

Idaho Transportation Department

Monthly WIM Distribution for May-2023

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	6	3,959	2,050	3	69	33	6	50	95	31	3	2	17	0
	Flex	.03	.00	.00	.50	.58	.61	1.06	.27	.89	.77	6.19	1.04	2.23	0.00
	Rigid	.06	.00	.00	.82	.61	.98	2.65	.33	1.65	1.80	6.76	2.18	3.57	0.00
	GVW	2.4	2.4	4.2	26.5	18.7	31.3	62.1	22.1	50.4	64.9	80.7	55.7	71.1	0.0
E	Num	6	2,031	1,056	1	33	19	2	25	46	17	1	2	9	0
	Flex	.03	.00	.00	.50	.53	.58	.54	.35	.85	.77	.42	.38	.61	0.00
	Rigid	.06	.00	.00	.77	.54	.94	1.30	.43	1.58	1.78	.40	.47	1.11	0.00
	GVW	1.8	2.4	4.2	26.0	18.9	31.7	51.9	22.7	51.5	66.5	41.9	36.8	56.3	0.0
W	Num	2	1,928	994	2	36	15	5	25	49	15	3	1	9	0
	Flex	.01	.00	.00	.45	.62	.67	1.08	.20	.92	.75	8.23	1.58	4.36	0.00
	Rigid	.03	.00	.00	.74	.67	1.10	2.70	.24	1.71	1.78	9.03	3.41	6.82	0.00
	GVW	7.1	2.4	4.2	26.0	18.4	30.8	62.0	21.6	49.1	61.8	92.4	74.2	88.8	0.0
E Lane1	Num	6	2,031	1,056	1	33	19	2	25	46	17	1	2	9	0
	Flex	.03	.00	.00	.50	.53	.58	.54	.35	.85	.77	.42	.38	.61	0.00
	Rigid	.06	.00	.00	.77	.54	.94	1.30	.43	1.58	1.78	.40	.47	1.11	0.00
	GVW	1.8	2.4	4.2	26.0	18.9	31.7	51.9	22.7	51.5	66.5	41.9	36.8	56.3	0.0
W Lane1	Num	2	1,928	994	2	36	15	5	25	49	15	3	1	9	0
	Flex	.01	.00	.00	.45	.62	.67	1.08	.20	.92	.75	8.23	1.58	4.36	0.00
	Rigid	.03	.00	.00	.74	.67	1.10	2.70	.24	1.71	1.78	9.03	3.41	6.82	0.00
	GVW	7.1	2.4	4.2	26.0	18.4	30.8	62.0	21.6	49.1	61.8	92.4	74.2	88.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2023

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9