

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2024

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	15	3,179	1,630	5	63	48	4	29	69	19	4	2	11	0
	Flex	.01	.00	.00	.45	.23	.29	.32	.21	.66	.74	2.10	.57	.87	0.00
	Rigid	.02	.00	.00	.50	.23	.51	.68	.23	1.26	1.80	2.10	.85	1.54	0.00
	GVW	9.9	2.7	3.9	22.5	16.2	29.6	50.1	23.0	53.9	78.1	64.9	56.0	77.9	0.0
E	Num	6	1,552	942	2	30	19	3	15	36	11	2	1	5	0
	Flex	.02	.00	.00	.66	.32	.41	.25	.28	.89	.95	1.70	.28	1.15	0.00
	Rigid	.03	.00	.00	.76	.32	.73	.62	.31	1.73	2.30	1.72	.40	2.18	0.00
	GVW	11.7	2.7	4.3	28.3	18.2	33.4	47.6	25.2	60.6	85.1	58.2	46.7	90.9	0.0
W	Num	9	1,628	688	3	33	29	2	14	32	8	3	1	5	0
	Flex	.01	.00	.00	.38	.15	.22	.39	.14	.41	.35	2.28	.70	.55	0.00
	Rigid	.02	.00	.00	.41	.15	.37	.67	.14	.75	.83	2.26	1.08	.82	0.00
	GVW	8.7	2.7	3.5	20.6	14.4	27.3	52.5	20.5	46.7	64.3	68.1	59.4	64.3	0.0
E Lane1	Num	6	1,552	942	2	30	19	3	15	36	11	2	1	5	0
	Flex	.02	.00	.00	.66	.32	.41	.25	.28	.89	.95	1.70	.28	1.15	0.00
	Rigid	.03	.00	.00	.76	.32	.73	.62	.31	1.73	2.30	1.72	.40	2.18	0.00
	GVW	11.7	2.7	4.3	28.3	18.2	33.4	47.6	25.2	60.6	85.1	58.2	46.7	90.9	0.0
W Lane1	Num	9	1,628	688	3	33	29	2	14	32	8	3	1	5	0
	Flex	.01	.00	.00	.38	.15	.22	.39	.14	.41	.35	2.28	.70	.55	0.00
	Rigid	.02	.00	.00	.41	.15	.37	.67	.14	.75	.83	2.26	1.08	.82	0.00
	GVW	8.7	2.7	3.5	20.6	14.4	27.3	52.5	20.5	46.7	64.3	68.1	59.4	64.3	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2024

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9