

Idaho Transportation Department

Monthly WIM Distribution for Apr-2015

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	882	651	18	158	9	2	13	458	20	1	1	20	0
	Flex	.00	.00	.00	1.82	.50	1.19	3.15	1.25	4.34	2.50	3.94	2.86	2.94	0.00
	Rigid	.00	.00	.00	2.52	.55	2.45	5.39	1.83	9.35	6.21	4.14	3.63	6.29	0.00
	GVW	2.1	4.3	6.9	31.3	18.0	40.2	77.1	38.1	90.3	95.4	72.4	81.1	104.3	0.0
SE	Num	1	418	349	10	68	5	2	7	263	10	1	1	6	0
	Flex	.00	.00	.00	2.03	.91	1.65	4.68	1.99	5.98	3.43	3.06	5.59	4.31	0.00
	Rigid	.00	.00	.00	2.93	.99	3.51	8.97	3.08	13.22	8.62	3.22	7.77	9.91	0.00
	GVW	1.2	3.7	6.3	31.5	19.6	43.7	78.9	42.7	101.1	100.9	66.2	102.9	106.5	0.0
NW	Num	2	464	302	8	90	5	1	6	195	10	1	1	14	0
	Flex	.00	.00	.00	1.47	.20	.69	2.99	.63	2.16	1.48	6.58	1.32	2.26	0.00
	Rigid	.00	.00	.00	1.97	.21	1.32	5.08	.80	4.18	3.66	6.88	1.50	4.56	0.00
	GVW	2.6	4.9	7.5	30.6	16.7	36.1	80.2	35.2	75.7	91.2	90.9	69.6	100.7	0.0
NW Lane1	Num	2	464	302	8	90	5	1	6	195	10	1	1	14	0
	Flex	.00	.00	.00	1.47	.20	.69	2.99	.63	2.16	1.48	6.58	1.32	2.26	0.00
	Rigid	.00	.00	.00	1.97	.21	1.32	5.08	.80	4.18	3.66	6.88	1.50	4.56	0.00
	GVW	2.6	4.9	7.5	30.6	16.7	36.1	80.2	35.2	75.7	91.2	90.9	69.6	100.7	0.0
SE Lane1	Num	1	418	349	10	68	5	2	7	263	10	1	1	6	0
	Flex	.00	.00	.00	2.03	.91	1.65	4.68	1.99	5.98	3.43	3.06	5.59	4.31	0.00
	Rigid	.00	.00	.00	2.93	.99	3.51	8.97	3.08	13.22	8.62	3.22	7.77	9.91	0.00
	GVW	1.2	3.7	6.3	31.5	19.6	43.7	78.9	42.7	101.1	100.9	66.2	102.9	106.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2015

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9