

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2017

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	614	585	14	42	11	2	11	352	15	1	1	15	0
	Flex	.00	.00	.00	.47	.23	.32	.16	.25	.69	.52	2.51	.33	.61	0.00
	Rigid	.00	.00	.00	.47	.24	.44	.52	.28	1.17	1.01	2.61	.35	1.08	0.00
	GVW	5.0	3.1	5.5	22.9	17.3	28.0	46.5	27.0	59.1	65.1	60.0	46.9	72.9	0.0
SE	Num	1	337	307	6	21	5	1	5	218	7	1	1	6	0
	Flex	.00	.00	.00	.30	.20	.30	.16	.28	.73	.50	1.62	.21	.49	0.00
	Rigid	.00	.00	.00	.31	.21	.41	.50	.31	1.26	.93	1.55	.23	.89	0.00
	GVW	4.9	3.0	5.5	21.4	16.5	26.6	46.1	27.6	61.0	63.5	64.8	42.9	67.0	0.0
NW	Num	1	304	290	8	22	6	1	6	142	8	1	1	9	0
	Flex	.00	.00	.00	.54	.26	.35	.15	.24	.64	.55	3.39	.67	.69	0.00
	Rigid	.00	.00	.00	.54	.26	.47	.58	.27	1.06	1.10	3.67	.72	1.19	0.00
	GVW	4.2	3.2	5.5	23.7	18.1	29.2	48.6	26.9	56.4	64.9	55.2	59.3	76.8	0.0
NW Lane1	Num	1	304	290	8	22	6	1	6	142	8	1	1	9	0
	Flex	.00	.00	.00	.54	.26	.35	.15	.24	.64	.55	3.39	.67	.69	0.00
	Rigid	.00	.00	.00	.54	.26	.47	.58	.27	1.06	1.10	3.67	.72	1.19	0.00
	GVW	4.2	3.2	5.5	23.7	18.1	29.2	48.6	26.9	56.4	64.9	55.2	59.3	76.8	0.0
SE Lane1	Num	1	337	307	6	21	5	1	5	218	7	1	1	6	0
	Flex	.00	.00	.00	.30	.20	.30	.16	.28	.73	.50	1.62	.21	.49	0.00
	Rigid	.00	.00	.00	.31	.21	.41	.50	.31	1.26	.93	1.55	.23	.89	0.00
	GVW	4.9	3.0	5.5	21.4	16.5	26.6	46.1	27.6	61.0	63.5	64.8	42.9	67.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2017

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9