

Idaho Transportation Department

Monthly WIM Distribution for May-2017

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	6	1,193	845	18	94	13	1	14	434	18	1	1	18	0
	Flex	.00	.00	.00	.52	.15	.52	.75	.38	1.17	.74	1.06	.47	.81	0.00
	Rigid	.00	.00	.00	.57	.15	.75	1.79	.41	2.06	1.50	1.03	.50	1.58	0.00
	GVW	2.6	3.3	6.1	23.9	17.6	29.6	54.6	31.1	65.2	68.6	51.6	54.4	80.4	0.0
SE	Num	3	598	421	9	52	6	1	8	248	9	1	1	9	0
	Flex	.00	.00	.00	.54	.15	.67	.25	.51	1.43	.87	1.10	.43	.82	0.00
	Rigid	.00	.00	.00	.61	.15	1.00	.50	.56	2.60	1.78	1.07	.46	1.69	0.00
	GVW	2.6	3.3	6.2	23.7	17.5	31.1	40.8	32.7	69.7	70.6	53.8	54.1	80.1	0.0
NW	Num	4	594	424	10	42	7	2	7	186	9	1	1	9	0
	Flex	.00	.00	.00	.48	.15	.44	1.32	.32	.79	.58	.40	.62	.81	0.00
	Rigid	.00	.00	.00	.52	.15	.63	3.33	.35	1.29	1.17	.37	.64	1.45	0.00
	GVW	2.7	3.2	6.0	23.8	17.7	29.5	67.8	30.8	58.7	64.3	41.4	57.3	80.0	0.0
NW Lane1	Num	4	594	424	10	42	7	2	7	186	9	1	1	9	0
	Flex	.00	.00	.00	.48	.15	.44	1.32	.32	.79	.58	.40	.62	.81	0.00
	Rigid	.00	.00	.00	.52	.15	.63	3.33	.35	1.29	1.17	.37	.64	1.45	0.00
	GVW	2.7	3.2	6.0	23.8	17.7	29.5	67.8	30.8	58.7	64.3	41.4	57.3	80.0	0.0
SE Lane1	Num	3	598	421	9	52	6	1	8	248	9	1	1	9	0
	Flex	.00	.00	.00	.54	.15	.67	.25	.51	1.43	.87	1.10	.43	.82	0.00
	Rigid	.00	.00	.00	.61	.15	1.00	.50	.56	2.60	1.78	1.07	.46	1.69	0.00
	GVW	2.6	3.3	6.2	23.7	17.5	31.1	40.8	32.7	69.7	70.6	53.8	54.1	80.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2017

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9