

Idaho Transportation Department

Monthly WIM Distribution for Jun-2017

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	12	1,260	947	15	135	23	4	17	462	29	0	2	15	0
	Flex	.00	.00	.00	.91	.14	.78	.81	.39	1.55	.87	0.00	.80	1.14	0.00
	Rigid	.00	.00	.00	1.17	.15	1.24	1.45	.43	2.84	1.80	0.00	.88	2.54	0.00
	GVW	2.1	3.4	6.2	27.7	17.4	33.7	57.3	30.0	67.8	67.6	0.0	56.9	85.0	0.0
SE	Num	6	624	459	7	78	11	2	9	263	15	0	1	9	0
	Flex	.00	.00	.00	1.25	.14	1.06	.75	.49	2.07	1.12	0.00	.94	1.31	0.00
	Rigid	.00	.00	.00	1.82	.14	1.76	1.63	.56	3.88	2.32	0.00	1.03	3.01	0.00
	GVW	2.0	3.5	6.3	28.8	17.1	36.7	58.8	30.4	73.0	69.6	0.0	59.2	87.4	0.0
NW	Num	6	637	488	9	57	12	2	8	198	15	0	1	7	0
	Flex	.00	.00	.00	.71	.14	.50	.65	.31	.88	.58	0.00	.43	.80	0.00
	Rigid	.00	.00	.00	.80	.15	.74	1.15	.33	1.47	1.19	0.00	.44	1.65	0.00
	GVW	2.1	3.3	6.1	27.0	17.8	30.7	54.8	29.9	60.5	63.9	0.0	49.7	81.1	0.0
NW Lane1	Num	6	637	488	9	57	12	2	8	198	15	0	1	7	0
	Flex	.00	.00	.00	.71	.14	.50	.65	.31	.88	.58	0.00	.43	.80	0.00
	Rigid	.00	.00	.00	.80	.15	.74	1.15	.33	1.47	1.19	0.00	.44	1.65	0.00
	GVW	2.1	3.3	6.1	27.0	17.8	30.7	54.8	29.9	60.5	63.9	0.0	49.7	81.1	0.0
SE Lane1	Num	6	624	459	7	78	11	2	9	263	15	0	1	9	0
	Flex	.00	.00	.00	1.25	.14	1.06	.75	.49	2.07	1.12	0.00	.94	1.31	0.00
	Rigid	.00	.00	.00	1.82	.14	1.76	1.63	.56	3.88	2.32	0.00	1.03	3.01	0.00
	GVW	2.0	3.5	6.3	28.8	17.1	36.7	58.8	30.4	73.0	69.6	0.0	59.2	87.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2017

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9