

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	26	1,435	1,102	22	192	48	5	21	436	20	1	2	13	0
	Flex	.00	.00	.00	1.21	.22	.83	.57	.53	1.92	.98	20.53	1.05	1.34	0.00
	Rigid	.00	.00	.00	1.46	.24	1.41	1.42	.60	3.59	2.00	24.52	1.15	2.90	0.00
	GVW	3.0	3.6	6.3	30.1	18.0	35.1	53.8	29.8	69.0	70.2	101.8	59.6	83.8	0.0
SE	Num	12	707	536	11	111	26	3	13	252	10	2	1	7	0
	Flex	.00	.00	.00	1.24	.20	1.08	.55	.58	2.47	1.12	21.02	1.31	1.28	0.00
	Rigid	.00	.00	.00	1.53	.22	1.94	1.50	.67	4.77	2.33	25.01	1.51	2.98	0.00
	GVW	3.0	3.7	6.2	29.9	17.7	38.5	53.8	29.8	73.2	72.1	108.7	61.4	79.2	0.0
NW	Num	13	728	566	11	81	22	3	8	184	10	1	1	6	0
	Flex	.00	.00	.00	1.10	.24	.60	.73	.48	1.20	.74	.19	.79	1.22	0.00
	Rigid	.00	.00	.00	1.28	.26	.91	1.47	.52	2.06	1.44	.18	.82	2.35	0.00
	GVW	3.0	3.4	6.3	29.8	18.4	31.8	54.2	30.3	63.0	66.1	37.8	58.4	86.4	0.0
NW Lane1	Num	13	728	566	11	81	22	3	8	184	10	1	1	6	0
	Flex	.00	.00	.00	1.10	.24	.60	.73	.48	1.20	.74	.19	.79	1.22	0.00
	Rigid	.00	.00	.00	1.28	.26	.91	1.47	.52	2.06	1.44	.18	.82	2.35	0.00
	GVW	3.0	3.4	6.3	29.8	18.4	31.8	54.2	30.3	63.0	66.1	37.8	58.4	86.4	0.0
SE Lane1	Num	12	707	536	11	111	26	3	13	252	10	2	1	7	0
	Flex	.00	.00	.00	1.24	.20	1.08	.55	.58	2.47	1.12	21.02	1.31	1.28	0.00
	Rigid	.00	.00	.00	1.53	.22	1.94	1.50	.67	4.77	2.33	25.01	1.51	2.98	0.00
	GVW	3.0	3.7	6.2	29.9	17.7	38.5	53.8	29.8	73.2	72.1	108.7	61.4	79.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9