

Idaho Transportation Department

Monthly WIM Distribution for Oct-2018

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	741	774	17	63	24	3	17	463	23	0	2	18	0
	Flex	.00	.00	.00	.16	.08	.19	.12	.09	.44	.23	0.00	.28	.26	0.00
	Rigid	.00	.00	.00	.16	.08	.31	.29	.09	.77	.46	0.00	.28	.53	0.00
	GVW	2.9	3.1	6.6	18.6	16.2	26.5	37.4	23.0	53.4	52.9	0.0	45.3	62.9	0.0
SE	Num	2	388	384	9	33	12	2	9	286	13	0	2	10	0
	Flex	.00	.00	.00	.19	.07	.26	.11	.08	.50	.26	0.00	.36	.31	0.00
	Rigid	.00	.00	.00	.20	.07	.44	.33	.09	.88	.52	0.00	.37	.63	0.00
	GVW	3.1	3.1	6.6	19.4	16.2	29.4	40.3	22.4	56.1	55.3	0.0	51.0	63.8	0.0
NW	Num	2	517	473	9	30	12	2	8	192	10	0	2	9	0
	Flex	.00	.00	.00	.12	.10	.13	.19	.08	.32	.20	0.00	.18	.21	0.00
	Rigid	.00	.00	.00	.12	.10	.19	.30	.09	.55	.38	0.00	.19	.41	0.00
	GVW	3.9	3.2	5.8	17.8	16.2	23.6	35.8	23.1	47.8	49.9	0.0	38.5	62.1	0.0
NW Lane1	Num	2	517	473	9	30	12	2	8	192	10	0	2	9	0
	Flex	.00	.00	.00	.12	.10	.13	.19	.08	.32	.20	0.00	.18	.21	0.00
	Rigid	.00	.00	.00	.12	.10	.19	.30	.09	.55	.38	0.00	.19	.41	0.00
	GVW	3.9	3.2	5.8	17.8	16.2	23.6	35.8	23.1	47.8	49.9	0.0	38.5	62.1	0.0
SE Lane1	Num	2	388	384	9	33	12	2	9	286	13	0	2	10	0
	Flex	.00	.00	.00	.19	.07	.26	.11	.08	.50	.26	0.00	.36	.31	0.00
	Rigid	.00	.00	.00	.20	.07	.44	.33	.09	.88	.52	0.00	.37	.63	0.00
	GVW	3.1	3.1	6.6	19.4	16.2	29.4	40.3	22.4	56.1	55.3	0.0	51.0	63.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2018

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9