

Idaho Transportation Department

Monthly WIM Distribution for Feb-2019

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	785	650	15	38	12	1	11	384	16	1	2	19	0
	Flex	.00	.00	.00	.19	.18	.14	.18	.12	.37	.24	1.24	.21	.32	0.00
	Rigid	.00	.00	.00	.19	.19	.19	.41	.14	.64	.46	1.19	.22	.57	0.00
	GVW	4.1	3.2	5.5	19.4	16.5	23.5	42.8	24.6	51.6	54.2	59.6	43.5	63.1	0.0
SE	Num	2	400	327	8	19	7	1	5	240	8	1	1	9	0
	Flex	.00	.00	.00	.17	.11	.12	.34	.15	.41	.23	1.24	.23	.33	0.00
	Rigid	.00	.00	.00	.18	.10	.17	.73	.17	.73	.44	1.19	.24	.55	0.00
	GVW	5.4	3.2	5.6	19.1	15.9	22.4	51.9	25.4	54.2	52.1	59.6	44.9	61.4	0.0
NW	Num	1	385	324	8	19	6	1	6	144	8	0	1	10	0
	Flex	.00	.00	.00	.19	.24	.15	.14	.10	.29	.24	0.00	.26	.32	0.00
	Rigid	.00	.00	.00	.19	.27	.21	.27	.11	.48	.46	0.00	.26	.57	0.00
	GVW	3.1	3.2	5.4	19.1	16.9	24.7	38.7	23.3	47.2	55.6	0.0	45.6	63.2	0.0
NW Lane1	Num	1	385	324	8	19	6	1	6	144	8	0	1	10	0
	Flex	.00	.00	.00	.19	.24	.15	.14	.10	.29	.24	0.00	.26	.32	0.00
	Rigid	.00	.00	.00	.19	.27	.21	.27	.11	.48	.46	0.00	.26	.57	0.00
	GVW	3.1	3.2	5.4	19.1	16.9	24.7	38.7	23.3	47.2	55.6	0.0	45.6	63.2	0.0
SE Lane1	Num	2	400	327	8	19	7	1	5	240	8	1	1	9	0
	Flex	.00	.00	.00	.17	.11	.12	.34	.15	.41	.23	1.24	.23	.33	0.00
	Rigid	.00	.00	.00	.18	.10	.17	.73	.17	.73	.44	1.19	.24	.55	0.00
	GVW	5.4	3.2	5.6	19.1	15.9	22.4	51.9	25.4	54.2	52.1	59.6	44.9	61.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2019

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9