

Idaho Transportation Department

Monthly WIM Distribution for Mar-2019

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	949	716	13	43	10	1	13	430	22	1	2	23	0
	Flex	.00	.00	.00	.20	.12	.16	.27	.12	.38	.21	.80	.31	.33	0.00
	Rigid	.00	.00	.00	.21	.12	.20	.44	.13	.65	.42	.75	.32	.55	0.00
	GVW	5.2	3.2	5.5	19.3	16.2	23.4	40.7	25.0	52.1	53.2	55.0	49.3	61.5	0.0
SE	Num	1	486	358	7	22	5	1	7	272	9	1	1	12	0
	Flex	.00	.00	.00	.20	.08	.12	.38	.15	.41	.23	.92	.35	.28	0.00
	Rigid	.00	.00	.00	.21	.07	.15	.59	.16	.73	.45	.87	.36	.48	0.00
	GVW	5.6	3.2	5.6	19.6	15.6	21.7	41.8	26.7	54.3	54.2	56.7	50.8	57.9	0.0
NW	Num	2	463	358	6	21	6	1	6	158	13	1	1	11	0
	Flex	.00	.00	.00	.21	.15	.19	.25	.09	.30	.19	.54	.26	.38	0.00
	Rigid	.00	.00	.00	.21	.16	.24	.40	.10	.50	.38	.51	.27	.63	0.00
	GVW	3.4	3.2	5.5	19.3	16.8	24.4	41.8	23.5	47.9	51.9	51.7	47.6	65.4	0.0
NW Lane1	Num	2	463	358	6	21	6	1	6	158	13	1	1	11	0
	Flex	.00	.00	.00	.21	.15	.19	.25	.09	.30	.19	.54	.26	.38	0.00
	Rigid	.00	.00	.00	.21	.16	.24	.40	.10	.50	.38	.51	.27	.63	0.00
	GVW	3.4	3.2	5.5	19.3	16.8	24.4	41.8	23.5	47.9	51.9	51.7	47.6	65.4	0.0
SE Lane1	Num	1	486	358	7	22	5	1	7	272	9	1	1	12	0
	Flex	.00	.00	.00	.20	.08	.12	.38	.15	.41	.23	.92	.35	.28	0.00
	Rigid	.00	.00	.00	.21	.07	.15	.59	.16	.73	.45	.87	.36	.48	0.00
	GVW	5.6	3.2	5.6	19.6	15.6	21.7	41.8	26.7	54.3	54.2	56.7	50.8	57.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2019

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9