

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2019

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,071	776	18	57	11	1	14	460	28	1	1	20	0
	Flex	.00	.00	.00	.18	.17	.18	.18	.11	.42	.21	.44	.41	.32	0.00
	Rigid	.00	.00	.00	.18	.18	.24	.31	.11	.74	.40	.41	.42	.59	0.00
	GVW	3.6	3.2	5.7	18.8	16.5	24.0	35.4	23.6	53.3	51.1	39.4	53.1	63.8	0.0
SE	Num	2	542	382	9	28	5	1	7	282	13	1	1	9	0
	Flex	.00	.00	.00	.16	.08	.15	.11	.11	.46	.20	.44	.43	.34	0.00
	Rigid	.00	.00	.00	.16	.07	.20	.29	.12	.82	.38	.42	.45	.56	0.00
	GVW	3.9	3.2	5.8	17.6	16.0	23.0	37.8	23.5	55.3	48.9	44.5	52.8	61.4	0.0
NW	Num	2	529	394	9	30	6	2	7	178	15	1	1	11	0
	Flex	.00	.00	.00	.19	.24	.22	.44	.10	.37	.21	.43	.37	.33	0.00
	Rigid	.00	.00	.00	.20	.27	.30	.58	.11	.61	.42	.41	.37	.64	0.00
	GVW	2.5	3.2	5.7	19.6	16.8	25.5	41.0	23.3	49.9	52.8	36.9	50.3	66.3	0.0
NW Lane1	Num	2	529	394	9	30	6	2	7	178	15	1	1	11	0
	Flex	.00	.00	.00	.19	.24	.22	.44	.10	.37	.21	.43	.37	.33	0.00
	Rigid	.00	.00	.00	.20	.27	.30	.58	.11	.61	.42	.41	.37	.64	0.00
	GVW	2.5	3.2	5.7	19.6	16.8	25.5	41.0	23.3	49.9	52.8	36.9	50.3	66.3	0.0
SE Lane1	Num	2	542	382	9	28	5	1	7	282	13	1	1	9	0
	Flex	.00	.00	.00	.16	.08	.15	.11	.11	.46	.20	.44	.43	.34	0.00
	Rigid	.00	.00	.00	.16	.07	.20	.29	.12	.82	.38	.42	.45	.56	0.00
	GVW	3.9	3.2	5.8	17.6	16.0	23.0	37.8	23.5	55.3	48.9	44.5	52.8	61.4	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2019

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9