

# Idaho Transportation Department

## Monthly WIM Distribution for May-2019

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	1,173	923	20	75	12	2	16	444	25	1	2	16	0
	Flex	.00	.00	.00	.25	.08	.25	.40	.12	.49	.29	.94	.39	.37	0.00
	Rigid	.00	.00	.00	.26	.08	.36	.70	.13	.86	.57	.88	.40	.69	0.00
	GVW	3.0	3.3	5.9	20.3	16.7	25.5	46.5	24.1	54.2	55.1	57.4	51.3	63.0	0.0
SE	Num	2	598	456	9	36	6	2	8	265	13	1	2	7	0
	Flex	.00	.00	.00	.27	.08	.26	.42	.13	.53	.30	.94	.47	.37	0.00
	Rigid	.00	.00	.00	.28	.08	.39	.75	.14	.94	.59	.88	.48	.70	0.00
	GVW	2.9	3.3	5.9	20.3	16.6	25.5	47.3	23.9	56.3	53.7	57.4	55.1	63.2	0.0
NW	Num	3	575	467	10	39	6	2	8	180	12	0	1	9	0
	Flex	.00	.00	.00	.24	.09	.26	.67	.12	.42	.28	0.00	.44	.44	0.00
	Rigid	.00	.00	.00	.25	.08	.37	1.23	.12	.70	.55	0.00	.45	.78	0.00
	GVW	2.9	3.3	5.9	20.3	16.8	26.4	51.4	23.7	50.8	56.7	0.0	51.9	63.7	0.0
NW Lane1	Num	3	575	467	10	39	6	2	8	180	12	0	1	9	0
	Flex	.00	.00	.00	.24	.09	.26	.67	.12	.42	.28	0.00	.44	.44	0.00
	Rigid	.00	.00	.00	.25	.08	.37	1.23	.12	.70	.55	0.00	.45	.78	0.00
	GVW	2.9	3.3	5.9	20.3	16.8	26.4	51.4	23.7	50.8	56.7	0.0	51.9	63.7	0.0
SE Lane1	Num	2	598	456	9	36	6	2	8	265	13	1	2	7	0
	Flex	.00	.00	.00	.27	.08	.26	.42	.13	.53	.30	.94	.47	.37	0.00
	Rigid	.00	.00	.00	.28	.08	.39	.75	.14	.94	.59	.88	.48	.70	0.00
	GVW	2.9	3.3	5.9	20.3	16.6	25.5	47.3	23.9	56.3	53.7	57.4	55.1	63.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for May-2019

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9