

Idaho Transportation Department

Monthly WIM Distribution for Jun-2019

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	10	1,357	1,091	19	96	18	3	17	470	24	2	2	15	0
	Flex	.00	.00	.00	.36	.10	.29	.26	.39	.60	.30	.72	.39	.39	0.00
	Rigid	.00	.00	.00	.38	.10	.44	.55	.44	1.07	.60	.69	.40	.78	0.00
	GVW	2.6	3.3	6.0	22.2	16.7	26.7	44.0	26.9	55.9	55.0	42.8	50.3	67.2	0.0
SE	Num	6	698	535	9	54	9	2	9	284	10	1	1	8	0
	Flex	.00	.00	.00	.41	.11	.34	.36	.18	.75	.38	.96	.55	.49	0.00
	Rigid	.00	.00	.00	.43	.11	.53	.75	.20	1.36	.81	.94	.55	.98	0.00
	GVW	2.6	3.4	6.2	22.1	17.0	27.2	47.5	26.9	59.8	60.6	51.7	56.9	72.1	0.0
NW	Num	5	658	555	10	42	9	2	9	187	15	1	1	7	0
	Flex	.00	.00	.00	.29	.09	.20	.25	.58	.38	.23	.09	.27	.32	0.00
	Rigid	.00	.00	.00	.30	.10	.28	.44	.66	.64	.43	.08	.27	.62	0.00
	GVW	2.8	3.2	5.9	21.7	16.5	25.2	42.3	26.6	50.0	50.7	27.5	45.6	62.5	0.0
NW Lane1	Num	5	658	555	10	42	9	2	9	187	15	1	1	7	0
	Flex	.00	.00	.00	.29	.09	.20	.25	.58	.38	.23	.09	.27	.32	0.00
	Rigid	.00	.00	.00	.30	.10	.28	.44	.66	.64	.43	.08	.27	.62	0.00
	GVW	2.8	3.2	5.9	21.7	16.5	25.2	42.3	26.6	50.0	50.7	27.5	45.6	62.5	0.0
SE Lane1	Num	6	698	535	9	54	9	2	9	284	10	1	1	8	0
	Flex	.00	.00	.00	.41	.11	.34	.36	.18	.75	.38	.96	.55	.49	0.00
	Rigid	.00	.00	.00	.43	.11	.53	.75	.20	1.36	.81	.94	.55	.98	0.00
	GVW	2.6	3.4	6.2	22.1	17.0	27.2	47.5	26.9	59.8	60.6	51.7	56.9	72.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2019

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9