

Idaho Transportation Department

Monthly WIM Distribution for Sep-2019

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	6	1,167	1,046	21	85	15	2	16	493	23	1	2	26	0
	Flex	.00	.00	.00	.25	.14	.24	.26	.17	.62	.39	.49	.27	.41	0.00
	Rigid	.00	.00	.00	.26	.14	.36	.50	.18	1.12	.81	.46	.28	.76	0.00
	GVW	2.2	3.3	5.9	19.9	16.8	25.2	44.5	25.3	55.6	57.5	49.2	44.4	63.3	0.0
SE	Num	2	586	513	9	49	6	1	8	303	12	1	2	17	0
	Flex	.00	.00	.00	.31	.12	.29	.12	.21	.78	.50	.49	.36	.47	0.00
	Rigid	.00	.00	.00	.32	.12	.43	.35	.23	1.43	1.04	.46	.38	.88	0.00
	GVW	1.2	3.5	6.1	20.2	16.8	25.8	39.5	26.3	59.7	60.7	49.2	47.4	64.2	0.0
NW	Num	5	581	533	12	36	9	2	8	190	11	0	1	9	0
	Flex	.00	.00	.00	.22	.16	.20	.27	.12	.36	.27	0.00	.18	.30	0.00
	Rigid	.00	.00	.00	.23	.17	.32	.51	.13	.62	.57	0.00	.18	.57	0.00
	GVW	2.5	3.2	5.8	19.7	16.9	24.7	44.6	24.1	48.8	54.9	0.0	42.7	62.3	0.0
NW Lane1	Num	5	581	533	12	36	9	2	8	190	11	0	1	9	0
	Flex	.00	.00	.00	.22	.16	.20	.27	.12	.36	.27	0.00	.18	.30	0.00
	Rigid	.00	.00	.00	.23	.17	.32	.51	.13	.62	.57	0.00	.18	.57	0.00
	GVW	2.5	3.2	5.8	19.7	16.9	24.7	44.6	24.1	48.8	54.9	0.0	42.7	62.3	0.0
SE Lane1	Num	2	586	513	9	49	6	1	8	303	12	1	2	17	0
	Flex	.00	.00	.00	.31	.12	.29	.12	.21	.78	.50	.49	.36	.47	0.00
	Rigid	.00	.00	.00	.32	.12	.43	.35	.23	1.43	1.04	.46	.38	.88	0.00
	GVW	1.2	3.5	6.1	20.2	16.8	25.8	39.5	26.3	59.7	60.7	49.2	47.4	64.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2019

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9