

Idaho Transportation Department

Monthly WIM Distribution for Oct-2019

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,007	1,005	22	65	16	2	15	430	26	1	2	20	0
	Flex	.00	.00	.00	.20	.11	.17	.10	.20	.42	.20	.27	.29	.26	0.00
	Rigid	.00	.00	.00	.22	.11	.23	.23	.23	.72	.40	.26	.31	.46	0.00
	GVW	3.7	3.3	5.9	20.3	16.6	24.4	34.8	24.4	52.5	50.1	27.0	46.7	56.6	0.0
SE	Num	2	534	498	9	35	7	1	7	265	11	0	1	12	0
	Flex	.00	.00	.00	.20	.09	.19	.09	.12	.47	.21	0.00	.50	.22	0.00
	Rigid	.00	.00	.00	.22	.08	.27	.22	.13	.82	.39	0.00	.51	.39	0.00
	GVW	2.8	3.3	6.0	20.7	16.6	25.0	34.0	24.8	54.9	49.3	0.0	55.1	53.0	0.0
NW	Num	2	491	524	12	31	10	2	8	165	15	1	2	9	0
	Flex	.00	.00	.00	.21	.12	.16	.09	.27	.33	.20	.27	.32	.30	0.00
	Rigid	.00	.00	.00	.22	.13	.22	.21	.31	.55	.40	.26	.33	.53	0.00
	GVW	4.0	3.2	5.8	20.0	16.6	24.6	34.5	23.8	48.5	50.4	27.0	47.0	59.7	0.0
NW Lane1	Num	2	491	524	12	31	10	2	8	165	15	1	2	9	0
	Flex	.00	.00	.00	.21	.12	.16	.09	.27	.33	.20	.27	.32	.30	0.00
	Rigid	.00	.00	.00	.22	.13	.22	.21	.31	.55	.40	.26	.33	.53	0.00
	GVW	4.0	3.2	5.8	20.0	16.6	24.6	34.5	23.8	48.5	50.4	27.0	47.0	59.7	0.0
SE Lane1	Num	2	534	498	9	35	7	1	7	265	11	0	1	12	0
	Flex	.00	.00	.00	.20	.09	.19	.09	.12	.47	.21	0.00	.50	.22	0.00
	Rigid	.00	.00	.00	.22	.08	.27	.22	.13	.82	.39	0.00	.51	.39	0.00
	GVW	2.8	3.3	6.0	20.7	16.6	25.0	34.0	24.8	54.9	49.3	0.0	55.1	53.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2019

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9