

Idaho Transportation Department

Monthly WIM Distribution for Nov-2019

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	940	823	17	51	19	1	13	421	23	1	2	18	0
	Flex	.00	.00	.00	.20	.11	.17	.14	.34	.42	.27	.02	.30	.30	0.00
	Rigid	.00	.00	.00	.21	.11	.24	.24	.39	.73	.55	.02	.31	.55	0.00
	GVW	4.8	3.3	5.7	19.7	16.6	24.3	37.8	25.2	52.4	56.8	17.7	49.9	62.3	0.0
SE	Num	1	484	409	8	26	7	1	7	262	10	1	1	10	0
	Flex	.00	.00	.00	.17	.08	.16	.12	.12	.47	.21	.00	.28	.27	0.00
	Rigid	.00	.00	.00	.18	.08	.23	.21	.13	.83	.42	.00	.29	.50	0.00
	GVW	5.5	3.3	5.7	19.0	16.5	23.9	33.4	24.9	54.7	53.4	11.2	48.1	59.5	0.0
NW	Num	1	455	414	9	25	12	1	7	160	14	1	1	8	0
	Flex	.01	.00	.00	.23	.13	.18	.16	.35	.34	.30	.05	.24	.34	0.00
	Rigid	.01	.00	.00	.25	.14	.26	.27	.40	.57	.62	.05	.25	.61	0.00
	GVW	4.9	3.3	5.6	20.6	16.7	25.0	40.3	25.2	48.4	58.8	24.1	45.9	65.2	0.0
NW Lane1	Num	1	455	414	9	25	12	1	7	160	14	1	1	8	0
	Flex	.01	.00	.00	.23	.13	.18	.16	.35	.34	.30	.05	.24	.34	0.00
	Rigid	.01	.00	.00	.25	.14	.26	.27	.40	.57	.62	.05	.25	.61	0.00
	GVW	4.9	3.3	5.6	20.6	16.7	25.0	40.3	25.2	48.4	58.8	24.1	45.9	65.2	0.0
SE Lane1	Num	1	484	409	8	26	7	1	7	262	10	1	1	10	0
	Flex	.00	.00	.00	.17	.08	.16	.12	.12	.47	.21	.00	.28	.27	0.00
	Rigid	.00	.00	.00	.18	.08	.23	.21	.13	.83	.42	.00	.29	.50	0.00
	GVW	5.5	3.3	5.7	19.0	16.5	23.9	33.4	24.9	54.7	53.4	11.2	48.1	59.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2019

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9