

Idaho Transportation Department

Monthly WIM Distribution for Dec-2019

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	855	724	15	31	10	1	12	345	17	1	2	18	0
	Flex	.00	.00	.00	.16	.14	.12	.53	.08	.36	.25	.64	.24	.29	0.00
	Rigid	.00	.00	.00	.16	.16	.14	1.32	.09	.62	.51	.60	.25	.47	0.00
	GVW	2.5	3.2	5.5	18.4	15.8	21.8	56.1	22.3	51.6	56.9	51.9	46.0	58.6	0.0
SE	Num	1	440	360	6	16	4	0	6	220	7	1	1	10	0
	Flex	.00	.00	.00	.12	.06	.13	0.00	.09	.38	.23	.56	.33	.23	0.00
	Rigid	.00	.00	.00	.12	.06	.17	0.00	.10	.67	.46	.53	.34	.37	0.00
	GVW	.7	3.2	5.5	17.4	15.4	21.8	0.0	22.5	53.3	54.3	50.9	49.4	52.7	0.0
NW	Num	1	415	364	9	16	7	1	7	125	10	1	2	8	0
	Flex	.00	.00	.00	.18	.23	.12	.53	.07	.32	.27	.71	.19	.36	0.00
	Rigid	.00	.00	.00	.18	.26	.14	1.32	.08	.53	.56	.67	.20	.60	0.00
	GVW	2.5	3.2	5.5	19.0	16.2	21.8	56.1	22.1	48.4	58.7	52.8	44.3	65.8	0.0
NW Lane1	Num	1	415	364	9	16	7	1	7	125	10	1	2	8	0
	Flex	.00	.00	.00	.18	.23	.12	.53	.07	.32	.27	.71	.19	.36	0.00
	Rigid	.00	.00	.00	.18	.26	.14	1.32	.08	.53	.56	.67	.20	.60	0.00
	GVW	2.5	3.2	5.5	19.0	16.2	21.8	56.1	22.1	48.4	58.7	52.8	44.3	65.8	0.0
SE Lane1	Num	1	440	360	6	16	4	0	6	220	7	1	1	10	0
	Flex	.00	.00	.00	.12	.06	.13	0.00	.09	.38	.23	.56	.33	.23	0.00
	Rigid	.00	.00	.00	.12	.06	.17	0.00	.10	.67	.46	.53	.34	.37	0.00
	GVW	.7	3.2	5.5	17.4	15.4	21.8	0.0	22.5	53.3	54.3	50.9	49.4	52.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2019

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9