

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2020

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	796	680	18	36	15	2	14	360	18	0	2	21	0
	Flex	.00	.00	.00	.21	.12	.15	.09	.11	.39	.30	0.00	.29	.32	0.00
	Rigid	.00	.00	.00	.22	.12	.20	.16	.14	.68	.60	0.00	.30	.53	0.00
	GVW	1.9	3.2	5.5	20.0	16.3	23.9	26.9	24.1	52.2	59.3	0.0	46.8	58.7	0.0
SE	Num	2	407	336	8	17	7	1	6	232	7	0	1	13	0
	Flex	.00	.00	.00	.15	.08	.15	.17	.14	.39	.25	0.00	.27	.25	0.00
	Rigid	.00	.00	.00	.16	.08	.19	.28	.17	.67	.47	0.00	.28	.40	0.00
	GVW	3.6	3.2	5.5	18.8	16.0	23.7	33.3	25.7	53.5	54.7	0.0	46.1	54.2	0.0
NW	Num	1	389	345	11	19	8	2	8	128	11	0	1	8	0
	Flex	.00	.00	.00	.24	.15	.16	.05	.09	.39	.32	0.00	.41	.43	0.00
	Rigid	.00	.00	.00	.24	.16	.21	.09	.11	.68	.67	0.00	.41	.76	0.00
	GVW	1.3	3.2	5.4	20.3	16.5	24.3	21.5	22.8	49.9	61.4	0.0	51.1	66.1	0.0
NW Lane1	Num	1	389	345	11	19	8	2	8	128	11	0	1	8	0
	Flex	.00	.00	.00	.24	.15	.16	.05	.09	.39	.32	0.00	.41	.43	0.00
	Rigid	.00	.00	.00	.24	.16	.21	.09	.11	.68	.67	0.00	.41	.76	0.00
	GVW	1.3	3.2	5.4	20.3	16.5	24.3	21.5	22.8	49.9	61.4	0.0	51.1	66.1	0.0
SE Lane1	Num	2	407	336	8	17	7	1	6	232	7	0	1	13	0
	Flex	.00	.00	.00	.15	.08	.15	.17	.14	.39	.25	0.00	.27	.25	0.00
	Rigid	.00	.00	.00	.16	.08	.19	.28	.17	.67	.47	0.00	.28	.40	0.00
	GVW	3.6	3.2	5.5	18.8	16.0	23.7	33.3	25.7	53.5	54.7	0.0	46.1	54.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2020

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9