

Idaho Transportation Department

Monthly WIM Distribution for Apr-2020

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	750	666	11	39	10	2	17	383	25	1	2	21	0
	Flex	.00	.00	.00	.39	.15	.19	.26	.39	.46	.29	.05	.32	.35	0.00
	Rigid	.00	.00	.00	.41	.16	.26	.45	.46	.80	.58	.05	.33	.66	0.00
	GVW	3.1	3.2	5.8	21.2	16.7	24.9	40.8	25.8	53.6	57.8	17.7	49.0	63.2	0.0
SE	Num	1	382	331	4	19	5	1	7	237	12	0	1	12	0
	Flex	.00	.00	.00	.17	.08	.15	.05	.12	.46	.24	0.00	.24	.28	0.00
	Rigid	.00	.00	.00	.17	.08	.19	.18	.14	.80	.46	0.00	.25	.49	0.00
	GVW	1.4	3.2	5.8	18.6	16.1	23.6	34.3	25.8	54.3	54.6	0.0	44.3	56.4	0.0
NW	Num	3	367	336	7	20	6	2	10	146	13	1	2	10	0
	Flex	.00	.00	.00	.55	.23	.22	.33	.48	.46	.34	.05	.31	.41	0.00
	Rigid	.00	.00	.00	.57	.25	.31	.53	.57	.78	.68	.05	.32	.80	0.00
	GVW	3.1	3.3	5.9	22.8	17.0	26.0	43.2	25.5	52.1	60.8	17.7	48.6	69.3	0.0
NW Lane1	Num	3	367	336	7	20	6	2	10	146	13	1	2	10	0
	Flex	.00	.00	.00	.55	.23	.22	.33	.48	.46	.34	.05	.31	.41	0.00
	Rigid	.00	.00	.00	.57	.25	.31	.53	.57	.78	.68	.05	.32	.80	0.00
	GVW	3.1	3.3	5.9	22.8	17.0	26.0	43.2	25.5	52.1	60.8	17.7	48.6	69.3	0.0
SE Lane1	Num	1	382	331	4	19	5	1	7	237	12	0	1	12	0
	Flex	.00	.00	.00	.17	.08	.15	.05	.12	.46	.24	0.00	.24	.28	0.00
	Rigid	.00	.00	.00	.17	.08	.19	.18	.14	.80	.46	0.00	.25	.49	0.00
	GVW	1.4	3.2	5.8	18.6	16.1	23.6	34.3	25.8	54.3	54.6	0.0	44.3	56.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2020

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9