

Idaho Transportation Department

Monthly WIM Distribution for May-2023

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	1,408	876	5	58	19	6	52	334	81	2	3	35	0
	Flex	.07	.00	.00	.74	.36	.49	.69	.17	1.16	.74	.61	.74	.90	0.00
	Rigid	.15	.01	.00	1.05	.37	.82	1.62	.20	2.16	1.81	.59	1.19	1.81	0.00
	GVW	7.8	2.6	4.3	39.8	17.9	31.3	59.9	23.3	63.8	80.0	47.4	60.1	84.3	0.0
SE	Num	3	662	443	3	30	10	5	24	180	66	2	2	15	0
	Flex	.01	.01	.00	.69	.28	.25	.54	.17	1.27	.70	.75	1.05	.63	0.00
	Rigid	.03	.01	.00	.94	.28	.38	1.23	.20	2.42	1.73	.73	1.72	1.29	0.00
	GVW	3.1	2.5	4.3	38.0	17.4	28.5	55.9	24.0	67.0	80.3	49.5	68.8	76.5	0.0
NW	Num	2	746	433	2	28	9	2	28	154	15	1	2	19	0
	Flex	.09	.00	.00	.74	.46	.73	1.10	.17	1.07	.93	.43	.18	1.14	0.00
	Rigid	.19	.00	.00	1.13	.48	1.28	2.62	.21	1.93	2.27	.41	.23	2.25	0.00
	GVW	9.0	2.6	4.3	42.7	18.5	33.7	70.1	23.0	60.0	80.4	42.8	35.5	90.8	0.0
NW Lane1	Num	2	746	433	2	28	9	2	28	154	15	1	2	19	0
	Flex	.09	.00	.00	.74	.46	.73	1.10	.17	1.07	.93	.43	.18	1.14	0.00
	Rigid	.19	.00	.00	1.13	.48	1.28	2.62	.21	1.93	2.27	.41	.23	2.25	0.00
	GVW	9.0	2.6	4.3	42.7	18.5	33.7	70.1	23.0	60.0	80.4	42.8	35.5	90.8	0.0
SE Lane1	Num	3	662	443	3	30	10	5	24	180	66	2	2	15	0
	Flex	.01	.01	.00	.69	.28	.25	.54	.17	1.27	.70	.75	1.05	.63	0.00
	Rigid	.03	.01	.00	.94	.28	.38	1.23	.20	2.42	1.73	.73	1.72	1.29	0.00
	GVW	3.1	2.5	4.3	38.0	17.4	28.5	55.9	24.0	67.0	80.3	49.5	68.8	76.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2023

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9