

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2024

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,116	788	8	56	16	4	40	390	42	3	4	32	0
	Flex	.10	.00	.00	1.08	.34	.36	.66	.17	1.12	.64	.90	.44	1.20	0.00
	Rigid	.21	.00	.00	1.37	.34	.59	1.35	.19	2.09	1.51	.85	.59	2.32	0.00
	GVW	14.4	2.4	4.1	38.1	17.7	28.8	57.4	24.3	65.6	74.3	53.4	46.9	91.4	0.0
SE	Num	1	562	399	4	29	7	3	19	246	27	2	3	12	0
	Flex	.19	.00	.00	.69	.23	.38	.69	.16	1.22	.56	1.24	.27	.86	0.00
	Rigid	.40	.00	.00	.90	.23	.63	1.18	.18	2.30	1.34	1.19	.30	1.73	0.00
	GVW	22.4	2.4	4.2	35.0	17.1	29.9	58.5	25.5	69.0	72.8	58.6	43.0	75.8	0.0
NW	Num	2	554	389	4	27	9	4	21	144	15	2	2	20	0
	Flex	.07	.00	.00	1.49	.45	.37	.76	.18	.99	.79	.51	.64	1.44	0.00
	Rigid	.16	.00	.00	1.86	.47	.61	1.63	.21	1.78	1.84	.48	.99	2.72	0.00
	GVW	11.2	2.4	4.0	39.9	18.3	28.2	61.5	23.5	59.6	76.9	47.2	53.6	100.2	0.0
NW Lane1	Num	2	554	389	4	27	9	4	21	144	15	2	2	20	0
	Flex	.07	.00	.00	1.49	.45	.37	.76	.18	.99	.79	.51	.64	1.44	0.00
	Rigid	.16	.00	.00	1.86	.47	.61	1.63	.21	1.78	1.84	.48	.99	2.72	0.00
	GVW	11.2	2.4	4.0	39.9	18.3	28.2	61.5	23.5	59.6	76.9	47.2	53.6	100.2	0.0
SE Lane1	Num	1	562	399	4	29	7	3	19	246	27	2	3	12	0
	Flex	.19	.00	.00	.69	.23	.38	.69	.16	1.22	.56	1.24	.27	.86	0.00
	Rigid	.40	.00	.00	.90	.23	.63	1.18	.18	2.30	1.34	1.19	.30	1.73	0.00
	GVW	22.4	2.4	4.2	35.0	17.1	29.9	58.5	25.5	69.0	72.8	58.6	43.0	75.8	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2024

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9