

Idaho Transportation Department

Monthly WIM Distribution for Feb-2017

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	641	612	9	33	13	7	6	108	43	2	2	13	0
	Flex	.00	.00	.00	.19	.29	.16	.06	.11	.27	.15	.27	.21	.25	0.00
	Rigid	.00	.00	.00	.20	.32	.21	.21	.11	.41	.32	.25	.22	.47	0.00
	GVW	2.8	3.3	5.7	20.1	17.5	24.0	36.6	23.7	43.6	50.6	39.2	39.3	60.4	0.0
N	Num	1	311	303	5	14	4	7	3	47	22	1	1	5	0
	Flex	.00	.00	.00	.14	.45	.19	.07	.10	.21	.16	.33	.05	.18	0.00
	Rigid	.00	.00	.00	.14	.52	.25	.24	.11	.32	.28	.31	.05	.31	0.00
	GVW	2.9	3.3	5.6	18.4	17.2	26.6	38.6	24.2	41.2	44.8	42.6	30.1	50.2	0.0
S	Num	1	329	309	5	19	9	1	4	61	21	1	1	8	0
	Flex	.00	.00	.00	.23	.16	.16	.03	.09	.32	.15	.14	.42	.29	0.00
	Rigid	.00	.00	.00	.25	.16	.19	.13	.10	.49	.37	.13	.44	.57	0.00
	GVW	2.7	3.4	5.8	21.5	17.7	23.1	30.2	22.3	45.7	56.7	34.3	47.5	66.9	0.0
N Lane1	Num	1	311	303	5	14	4	7	3	47	22	1	1	5	0
	Flex	.00	.00	.00	.14	.45	.19	.07	.10	.21	.16	.33	.05	.18	0.00
	Rigid	.00	.00	.00	.14	.52	.25	.24	.11	.32	.28	.31	.05	.31	0.00
	GVW	2.9	3.3	5.6	18.4	17.2	26.6	38.6	24.2	41.2	44.8	42.6	30.1	50.2	0.0
S Lane1	Num	1	329	309	5	19	9	1	4	61	21	1	1	8	0
	Flex	.00	.00	.00	.23	.16	.16	.03	.09	.32	.15	.14	.42	.29	0.00
	Rigid	.00	.00	.00	.25	.16	.19	.13	.10	.49	.37	.13	.44	.57	0.00
	GVW	2.7	3.4	5.8	21.5	17.7	23.1	30.2	22.3	45.7	56.7	34.3	47.5	66.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2017

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9