

Idaho Transportation Department

Monthly WIM Distribution for Mar-2017

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	754	686	9	37	12	1	7	108	42	1	2	13	0
	Flex	.00	.00	.00	.23	.22	.19	.18	.13	.31	.20	.59	.49	.29	0.00
	Rigid	.00	.00	.00	.26	.24	.28	.41	.14	.48	.43	.56	.50	.56	0.00
	GVW	3.4	3.3	5.9	21.4	17.3	25.0	41.1	24.3	44.9	54.3	45.9	48.0	61.9	0.0
N	Num	1	346	339	5	17	5	1	3	46	21	1	1	6	0
	Flex	.00	.00	.00	.21	.31	.24	.28	.18	.27	.20	.45	.09	.28	0.00
	Rigid	.00	.00	.00	.23	.34	.35	.57	.19	.43	.36	.42	.09	.52	0.00
	GVW	2.8	3.3	5.8	21.0	17.2	26.4	44.7	26.1	43.0	47.2	37.9	35.0	56.7	0.0
S	Num	2	408	347	4	20	7	2	4	62	21	2	1	8	0
	Flex	.00	.00	.00	.25	.15	.18	.12	.10	.34	.19	.74	.96	.31	0.00
	Rigid	.00	.00	.00	.28	.16	.26	.30	.11	.53	.49	.70	.97	.60	0.00
	GVW	3.3	3.4	6.0	21.2	17.3	25.2	38.9	23.3	46.5	61.6	49.7	61.9	66.0	0.0
N Lane1	Num	1	346	339	5	17	5	1	3	46	21	1	1	6	0
	Flex	.00	.00	.00	.21	.31	.24	.28	.18	.27	.20	.45	.09	.28	0.00
	Rigid	.00	.00	.00	.23	.34	.35	.57	.19	.43	.36	.42	.09	.52	0.00
	GVW	2.8	3.3	5.8	21.0	17.2	26.4	44.7	26.1	43.0	47.2	37.9	35.0	56.7	0.0
S Lane1	Num	2	408	347	4	20	7	2	4	62	21	2	1	8	0
	Flex	.00	.00	.00	.25	.15	.18	.12	.10	.34	.19	.74	.96	.31	0.00
	Rigid	.00	.00	.00	.28	.16	.26	.30	.11	.53	.49	.70	.97	.60	0.00
	GVW	3.3	3.4	6.0	21.2	17.3	25.2	38.9	23.3	46.5	61.6	49.7	61.9	66.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2017

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9