

Idaho Transportation Department

Monthly WIM Distribution for Jun-2017

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	16	871	794	12	159	28	5	12	102	45	1	1	11	0
	Flex	.00	.00	.00	.86	.19	.34	.21	.21	.53	.48	1.08	.23	.40	0.00
	Rigid	.00	.00	.00	.99	.21	.50	.72	.26	.88	1.01	1.13	.24	.94	0.00
	GVW	3.0	3.6	6.1	25.0	16.7	26.8	46.0	23.8	45.0	57.4	32.4	42.4	62.8	0.0
N	Num	6	426	410	6	80	12	2	6	45	22	1	1	5	0
	Flex	.00	.00	.00	.75	.19	.32	.09	.20	.53	.61	.08	.21	.40	0.00
	Rigid	.00	.00	.00	.88	.21	.45	.35	.24	.91	1.23	.08	.22	1.06	0.00
	GVW	2.8	3.6	6.4	23.2	16.6	25.7	37.7	22.8	43.3	51.2	21.8	41.9	62.9	0.0
S	Num	10	445	398	6	83	16	4	6	60	23	1	1	6	0
	Flex	.00	.00	.00	.98	.18	.36	.23	.21	.56	.35	6.09	.14	.39	0.00
	Rigid	.00	.00	.00	1.11	.20	.53	.78	.26	.91	.81	6.43	.15	.84	0.00
	GVW	3.1	3.5	6.1	27.2	16.7	27.8	47.7	24.2	47.9	64.9	87.9	35.7	63.3	0.0
N Lane1	Num	6	426	410	6	80	12	2	6	45	22	1	1	5	0
	Flex	.00	.00	.00	.75	.19	.32	.09	.20	.53	.61	.08	.21	.40	0.00
	Rigid	.00	.00	.00	.88	.21	.45	.35	.24	.91	1.23	.08	.22	1.06	0.00
	GVW	2.8	3.6	6.4	23.2	16.6	25.7	37.7	22.8	43.3	51.2	21.8	41.9	62.9	0.0
S Lane1	Num	10	445	398	6	83	16	4	6	60	23	1	1	6	0
	Flex	.00	.00	.00	.98	.18	.36	.23	.21	.56	.35	6.09	.14	.39	0.00
	Rigid	.00	.00	.00	1.11	.20	.53	.78	.26	.91	.81	6.43	.15	.84	0.00
	GVW	3.1	3.5	6.1	27.2	16.7	27.8	47.7	24.2	47.9	64.9	87.9	35.7	63.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2017

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9