

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	45	1,186	1,061	14	198	60	8	12	90	35	1	1	7	0
	Flex	.00	.00	.00	1.28	.22	.47	.26	.47	.80	.70	.01	.06	.23	0.00
	Rigid	.00	.00	.00	1.51	.24	.72	.81	.53	1.37	1.47	.01	.06	.58	0.00
	GVW	3.5	3.9	6.3	27.7	16.8	30.8	44.1	23.7	45.9	57.2	14.3	29.8	47.4	0.0
N	Num	14	562	508	7	98	19	4	7	45	20	1	1	4	0
	Flex	.00	.00	.00	1.00	.19	.65	.50	.25	.97	.97	.01	.06	.33	0.00
	Rigid	.00	.00	.00	1.19	.20	.98	1.15	.28	1.69	1.93	.01	.06	.78	0.00
	GVW	3.5	4.1	6.2	26.6	16.8	30.6	42.0	21.7	45.0	57.0	14.3	29.8	47.6	0.0
S	Num	31	624	553	7	100	41	6	5	45	16	0	0	4	0
	Flex	.00	.00	.00	1.53	.25	.38	.22	.75	.59	.29	0.00	0.00	.16	0.00
	Rigid	.00	.00	.00	1.78	.27	.59	.80	.87	.98	.73	0.00	0.00	.49	0.00
	GVW	3.6	3.8	6.4	29.1	16.8	30.7	46.4	27.6	46.2	56.2	0.0	0.0	51.1	0.0
N Lane1	Num	14	562	508	7	98	19	4	7	45	20	1	1	4	0
	Flex	.00	.00	.00	1.00	.19	.65	.50	.25	.97	.97	.01	.06	.33	0.00
	Rigid	.00	.00	.00	1.19	.20	.98	1.15	.28	1.69	1.93	.01	.06	.78	0.00
	GVW	3.5	4.1	6.2	26.6	16.8	30.6	42.0	21.7	45.0	57.0	14.3	29.8	47.6	0.0
S Lane1	Num	31	624	553	7	100	41	6	5	45	16	0	0	4	0
	Flex	.00	.00	.00	1.53	.25	.38	.22	.75	.59	.29	0.00	0.00	.16	0.00
	Rigid	.00	.00	.00	1.78	.27	.59	.80	.87	.98	.73	0.00	0.00	.49	0.00
	GVW	3.6	3.8	6.4	29.1	16.8	30.7	46.4	27.6	46.2	56.2	0.0	0.0	51.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9