

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2017

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	983	1,123	13	93	20	3	10	118	52	0	2	12	0
	Flex	.00	.00	.00	.22	.11	.21	.12	.16	.32	.20	0.00	.30	.29	0.00
	Rigid	.00	.00	.00	.24	.11	.31	.45	.18	.50	.43	0.00	.32	.58	0.00
	GVW	2.9	3.5	6.5	21.1	16.9	25.3	43.0	24.4	44.2	53.9	0.0	44.7	60.6	0.0
N	Num	2	476	579	7	33	11	1	5	54	26	0	1	6	0
	Flex	.00	.00	.00	.23	.07	.13	.07	.16	.21	.18	0.00	.20	.29	0.00
	Rigid	.00	.00	.00	.24	.07	.17	.23	.20	.33	.34	0.00	.21	.50	0.00
	GVW	2.4	3.3	6.4	21.1	16.4	22.2	36.2	27.0	40.0	46.4	0.0	44.9	58.5	0.0
S	Num	3	507	544	5	60	10	2	6	65	26	0	1	7	0
	Flex	.00	.00	.00	.21	.13	.30	.13	.15	.41	.21	0.00	.27	.31	0.00
	Rigid	.00	.00	.00	.24	.14	.46	.48	.16	.64	.53	0.00	.28	.66	0.00
	GVW	3.2	3.6	6.6	20.8	17.2	28.7	44.4	22.3	47.5	61.5	0.0	40.8	63.6	0.0
N Lane1	Num	2	476	579	7	33	11	1	5	54	26	0	1	6	0
	Flex	.00	.00	.00	.23	.07	.13	.07	.16	.21	.18	0.00	.20	.29	0.00
	Rigid	.00	.00	.00	.24	.07	.17	.23	.20	.33	.34	0.00	.21	.50	0.00
	GVW	2.4	3.3	6.4	21.1	16.4	22.2	36.2	27.0	40.0	46.4	0.0	44.9	58.5	0.0
S Lane1	Num	3	507	544	5	60	10	2	6	65	26	0	1	7	0
	Flex	.00	.00	.00	.21	.13	.30	.13	.15	.41	.21	0.00	.27	.31	0.00
	Rigid	.00	.00	.00	.24	.14	.46	.48	.16	.64	.53	0.00	.28	.66	0.00
	GVW	3.2	3.6	6.6	20.8	17.2	28.7	44.4	22.3	47.5	61.5	0.0	40.8	63.6	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2017

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9