

Idaho Transportation Department

Monthly WIM Distribution for Jan-2018

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	0	1	1	1	0	0	0	0	1	0	0	0	0	0
	Flex	0.00	.00	.00	.13	0.00	0.00	0.00	0.00	.23	0.00	0.00	0.00	0.00	0.00
	Rigid	0.00	.00	.00	.16	0.00	0.00	0.00	0.00	.37	0.00	0.00	0.00	0.00	0.00
	GVW	0.0	3.9	5.7	26.4	0.0	0.0	0.0	0.0	43.7	0.0	0.0	0.0	0.0	0.0
N	Num	0	1	1	1	0	0	0	0	1	0	0	0	0	0
	Flex	0.00	.00	.00	.13	0.00	0.00	0.00	0.00	.23	0.00	0.00	0.00	0.00	0.00
	Rigid	0.00	.00	.00	.16	0.00	0.00	0.00	0.00	.37	0.00	0.00	0.00	0.00	0.00
	GVW	0.0	3.9	5.7	26.4	0.0	0.0	0.0	0.0	43.7	0.0	0.0	0.0	0.0	0.0
S	Num	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Flex	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Rigid	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	GVW	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
N Lane1	Num	0	1	1	1	0	0	0	0	1	0	0	0	0	0
	Flex	0.00	.00	.00	.13	0.00	0.00	0.00	0.00	.23	0.00	0.00	0.00	0.00	0.00
	Rigid	0.00	.00	.00	.16	0.00	0.00	0.00	0.00	.37	0.00	0.00	0.00	0.00	0.00
	GVW	0.0	3.9	5.7	26.4	0.0	0.0	0.0	0.0	43.7	0.0	0.0	0.0	0.0	0.0
S Lane1	Num	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Flex	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Rigid	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	GVW	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2018

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9