

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2018

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	1	1	1	0	0	0	0	1	1	0	0	0	0
	Flex	.00	.00	.00	.44	0.00	0.00	0.00	0.00	.60	.55	0.00	0.00	0.00	0.00
	Rigid	.00	.00	.00	.41	0.00	0.00	0.00	0.00	.82	1.10	0.00	0.00	0.00	0.00
	GVW	3.7	3.7	5.5	23.2	0.0	0.0	0.0	0.0	44.7	72.4	0.0	0.0	0.0	0.0
N	Num	1	1	1	1	0	0	0	0	1	1	0	0	0	0
	Flex	.00	.00	.00	.44	0.00	0.00	0.00	0.00	.60	.55	0.00	0.00	0.00	0.00
	Rigid	.00	.00	.00	.41	0.00	0.00	0.00	0.00	.82	1.10	0.00	0.00	0.00	0.00
	GVW	3.7	3.7	5.5	23.2	0.0	0.0	0.0	0.0	44.7	72.4	0.0	0.0	0.0	0.0
S	Num	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Flex	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Rigid	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	GVW	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
N Lane1	Num	1	1	1	1	0	0	0	0	1	1	0	0	0	0
	Flex	.00	.00	.00	.44	0.00	0.00	0.00	0.00	.60	.55	0.00	0.00	0.00	0.00
	Rigid	.00	.00	.00	.41	0.00	0.00	0.00	0.00	.82	1.10	0.00	0.00	0.00	0.00
	GVW	3.7	3.7	5.5	23.2	0.0	0.0	0.0	0.0	44.7	72.4	0.0	0.0	0.0	0.0
S Lane1	Num	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Flex	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Rigid	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	GVW	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2018

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9