

Idaho Transportation Department

Monthly WIM Distribution for Oct-2018

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	5	804	868	15	389	19	2	24	107	47	0	1	16	0
	Flex	.00	.00	.00	1.06	.11	.46	.54	.29	.97	.77	0.00	.49	.85	0.00
	Rigid	.00	.00	.00	1.32	.12	.82	1.46	.38	1.68	1.78	0.00	.62	1.87	0.00
	GVW	2.5	5.1	8.1	29.7	16.1	30.0	58.7	24.9	58.8	75.1	0.0	60.3	81.9	0.0
N	Num	2	390	410	8	186	7	2	12	47	24	0	0	6	0
	Flex	.00	.00	.00	1.24	.11	.56	.51	.37	.83	.87	0.00	0.00	1.19	0.00
	Rigid	.00	.00	.00	1.44	.12	.94	1.29	.52	1.40	1.80	0.00	0.00	2.40	0.00
	GVW	2.3	5.2	8.2	28.4	15.6	32.2	59.0	26.3	56.7	67.5	0.0	0.0	85.9	0.0
S	Num	4	519	484	7	203	13	2	12	60	24	0	1	9	0
	Flex	.00	.00	.00	.99	.11	.41	.54	.19	1.07	.65	0.00	.49	.58	0.00
	Rigid	.00	.00	.00	1.26	.12	.75	1.50	.21	1.91	1.74	0.00	.62	1.43	0.00
	GVW	2.6	4.8	7.7	29.4	16.5	29.0	58.4	23.4	60.4	82.5	0.0	60.3	77.3	0.0
N Lane1	Num	2	390	410	8	186	7	2	12	47	24	0	0	6	0
	Flex	.00	.00	.00	1.24	.11	.56	.51	.37	.83	.87	0.00	0.00	1.19	0.00
	Rigid	.00	.00	.00	1.44	.12	.94	1.29	.52	1.40	1.80	0.00	0.00	2.40	0.00
	GVW	2.3	5.2	8.2	28.4	15.6	32.2	59.0	26.3	56.7	67.5	0.0	0.0	85.9	0.0
S Lane1	Num	4	519	484	7	203	13	2	12	60	24	0	1	9	0
	Flex	.00	.00	.00	.99	.11	.41	.54	.19	1.07	.65	0.00	.49	.58	0.00
	Rigid	.00	.00	.00	1.26	.12	.75	1.50	.21	1.91	1.74	0.00	.62	1.43	0.00
	GVW	2.6	4.8	7.7	29.4	16.5	29.0	58.4	23.4	60.4	82.5	0.0	60.3	77.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2018

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9