

Idaho Transportation Department

Monthly WIM Distribution for Nov-2018

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	903	628	8	355	18	2	20	107	51	2	1	15	0
	Flex	.00	.00	.01	1.43	.12	.82	.61	.42	1.32	.83	4.57	1.54	1.19	0.00
	Rigid	.00	.00	.01	1.92	.12	1.55	1.94	.59	2.46	1.98	4.93	1.75	2.67	0.00
	GVW	3.3	5.4	8.1	32.7	15.2	36.5	62.9	26.5	63.9	75.9	72.8	69.9	88.9	0.0
N	Num	1	439	309	5	170	7	1	9	50	25	1	1	7	0
	Flex	.00	.00	.01	1.38	.10	.77	.63	.63	1.04	.90	1.43	1.80	1.50	0.00
	Rigid	.00	.00	.01	1.86	.11	1.30	2.17	.91	1.90	1.92	1.41	1.97	3.08	0.00
	GVW	4.0	5.5	8.2	34.2	14.8	37.4	65.8	29.9	60.6	69.8	56.8	70.3	92.8	0.0
S	Num	2	464	319	4	185	11	2	11	57	26	1	1	9	0
	Flex	.00	.00	.00	1.57	.13	.93	.61	.26	1.57	.80	12.87	1.00	.96	0.00
	Rigid	.00	.00	.00	2.15	.14	1.83	1.94	.30	2.98	2.11	14.35	1.31	2.32	0.00
	GVW	2.4	5.3	7.9	31.8	15.5	37.3	62.8	24.6	66.8	82.0	107.7	69.1	85.5	0.0
N Lane1	Num	1	439	309	5	170	7	1	9	50	25	1	1	7	0
	Flex	.00	.00	.01	1.38	.10	.77	.63	.63	1.04	.90	1.43	1.80	1.50	0.00
	Rigid	.00	.00	.01	1.86	.11	1.30	2.17	.91	1.90	1.92	1.41	1.97	3.08	0.00
	GVW	4.0	5.5	8.2	34.2	14.8	37.4	65.8	29.9	60.6	69.8	56.8	70.3	92.8	0.0
S Lane1	Num	2	464	319	4	185	11	2	11	57	26	1	1	9	0
	Flex	.00	.00	.00	1.57	.13	.93	.61	.26	1.57	.80	12.87	1.00	.96	0.00
	Rigid	.00	.00	.00	2.15	.14	1.83	1.94	.30	2.98	2.11	14.35	1.31	2.32	0.00
	GVW	2.4	5.3	7.9	31.8	15.5	37.3	62.8	24.6	66.8	82.0	107.7	69.1	85.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2018

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9