

Idaho Transportation Department

Monthly WIM Distribution for Feb-2019

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	3	653	358	8	336	23	6	14	99	42	1	1	9	0
	Flex	.00	.00	.01	2.70	.17	1.38	.79	.57	1.96	1.44	6.43	2.81	1.78	0.00
	Rigid	.00	.00	.01	3.49	.19	2.83	2.50	.77	3.83	3.51	6.89	4.03	3.97	0.00
	GVW	3.1	6.0	8.2	34.6	14.4	44.7	67.5	31.5	71.6	86.0	86.6	77.3	96.8	0.0
N	Num	2	313	161	4	176	12	1	7	41	22	1	1	3	0
	Flex	.00	.00	.01	2.99	.15	1.17	1.48	.64	2.24	1.68	6.43	3.98	3.14	0.00
	Rigid	.00	.00	.01	3.80	.16	2.36	4.93	.86	4.43	3.84	6.89	5.76	6.02	0.00
	GVW	3.7	6.2	8.5	35.5	14.1	43.1	80.7	32.8	73.9	79.5	86.6	85.1	104.1	0.0
S	Num	2	341	197	4	160	10	6	6	58	20	0	1	7	0
	Flex	.00	.00	.01	2.10	.20	1.64	.76	.46	1.77	1.24	0.00	.46	1.33	0.00
	Rigid	.00	.00	.01	2.80	.21	3.39	2.40	.60	3.43	3.30	0.00	.59	3.24	0.00
	GVW	2.6	5.9	7.9	33.0	14.7	46.7	66.7	30.3	70.0	94.0	0.0	61.8	94.1	0.0
N Lane1	Num	2	313	161	4	176	12	1	7	41	22	1	1	3	0
	Flex	.00	.00	.01	2.99	.15	1.17	1.48	.64	2.24	1.68	6.43	3.98	3.14	0.00
	Rigid	.00	.00	.01	3.80	.16	2.36	4.93	.86	4.43	3.84	6.89	5.76	6.02	0.00
	GVW	3.7	6.2	8.5	35.5	14.1	43.1	80.7	32.8	73.9	79.5	86.6	85.1	104.1	0.0
S Lane1	Num	2	341	197	4	160	10	6	6	58	20	0	1	7	0
	Flex	.00	.00	.01	2.10	.20	1.64	.76	.46	1.77	1.24	0.00	.46	1.33	0.00
	Rigid	.00	.00	.01	2.80	.21	3.39	2.40	.60	3.43	3.30	0.00	.59	3.24	0.00
	GVW	2.6	5.9	7.9	33.0	14.7	46.7	66.7	30.3	70.0	94.0	0.0	61.8	94.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2019

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9