

Idaho Transportation Department

Monthly WIM Distribution for Mar-2019

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	868	429	10	409	13	4	18	110	45	1	1	14	0
	Flex	.00	.00	.01	2.73	.17	.87	1.08	.61	2.16	1.40	2.44	.87	1.88	0.00
	Rigid	.00	.00	.01	3.77	.18	1.69	3.22	.72	4.28	3.46	2.45	1.25	4.07	0.00
	GVW	3.2	6.1	8.1	36.0	15.1	39.2	66.8	27.3	72.6	87.8	66.9	64.7	95.0	0.0
N	Num	1	433	207	5	212	6	1	10	46	23	1	1	5	0
	Flex	.00	.00	.01	2.66	.13	1.11	1.22	.53	2.15	1.60	4.26	.86	2.72	0.00
	Rigid	.00	.00	.01	3.52	.14	2.25	2.50	.62	4.23	3.65	4.32	1.26	5.27	0.00
	GVW	3.3	6.2	8.4	35.6	14.9	40.6	67.2	27.0	72.8	79.2	81.2	64.9	96.9	0.0
S	Num	2	435	221	5	197	8	5	8	64	22	1	1	9	0
	Flex	.00	.00	.01	2.74	.20	.65	1.21	.78	2.19	1.24	.63	.38	1.60	0.00
	Rigid	.00	.00	.01	3.85	.22	1.21	3.68	.92	4.34	3.35	.59	.42	3.76	0.00
	GVW	2.9	5.9	7.9	36.2	15.3	37.7	68.9	28.1	72.5	97.2	52.6	54.9	96.6	0.0
N Lane1	Num	1	433	207	5	212	6	1	10	46	23	1	1	5	0
	Flex	.00	.00	.01	2.66	.13	1.11	1.22	.53	2.15	1.60	4.26	.86	2.72	0.00
	Rigid	.00	.00	.01	3.52	.14	2.25	2.50	.62	4.23	3.65	4.32	1.26	5.27	0.00
	GVW	3.3	6.2	8.4	35.6	14.9	40.6	67.2	27.0	72.8	79.2	81.2	64.9	96.9	0.0
S Lane1	Num	2	435	221	5	197	8	5	8	64	22	1	1	9	0
	Flex	.00	.00	.01	2.74	.20	.65	1.21	.78	2.19	1.24	.63	.38	1.60	0.00
	Rigid	.00	.00	.01	3.85	.22	1.21	3.68	.92	4.34	3.35	.59	.42	3.76	0.00
	GVW	2.9	5.9	7.9	36.2	15.3	37.7	68.9	28.1	72.5	97.2	52.6	54.9	96.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2019

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9