

Idaho Transportation Department

Monthly WIM Distribution for May-2019

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	9	978	501	12	630	18	3	36	114	51	0	1	16	0
	Flex	.00	.00	.01	3.64	.24	1.68	1.22	.66	3.19	2.59	0.00	3.25	1.92	0.00
	Rigid	.00	.00	.01	4.60	.26	3.44	3.60	.89	6.46	6.84	0.00	4.35	5.28	0.00
	GVW	3.4	6.0	8.0	34.2	17.4	43.4	67.7	28.0	75.3	96.5	0.0	86.4	99.2	0.0
N	Num	4	474	239	6	329	7	3	20	48	25	0	1	7	0
	Flex	.00	.00	.01	3.54	.23	1.62	1.32	.65	3.25	2.88	0.00	2.52	2.28	0.00
	Rigid	.00	.00	.01	4.57	.25	3.34	3.61	.93	6.43	7.18	0.00	3.03	5.51	0.00
	GVW	4.0	6.2	8.3	35.6	17.6	44.0	74.7	28.0	75.4	90.2	0.0	83.2	99.0	0.0
S	Num	5	504	262	6	302	11	2	16	67	25	0	1	8	0
	Flex	.00	.00	.01	3.45	.26	1.73	.97	.73	3.15	2.42	0.00	2.90	1.61	0.00
	Rigid	.00	.00	.01	4.27	.29	3.53	3.03	.90	6.49	6.77	0.00	3.96	4.67	0.00
	GVW	3.1	5.8	7.7	32.6	17.2	43.5	61.7	28.1	75.2	103.3	0.0	84.1	97.2	0.0
N Lane1	Num	4	474	239	6	329	7	3	20	48	25	0	1	7	0
	Flex	.00	.00	.01	3.54	.23	1.62	1.32	.65	3.25	2.88	0.00	2.52	2.28	0.00
	Rigid	.00	.00	.01	4.57	.25	3.34	3.61	.93	6.43	7.18	0.00	3.03	5.51	0.00
	GVW	4.0	6.2	8.3	35.6	17.6	44.0	74.7	28.0	75.4	90.2	0.0	83.2	99.0	0.0
S Lane1	Num	5	504	262	6	302	11	2	16	67	25	0	1	8	0
	Flex	.00	.00	.01	3.45	.26	1.73	.97	.73	3.15	2.42	0.00	2.90	1.61	0.00
	Rigid	.00	.00	.01	4.27	.29	3.53	3.03	.90	6.49	6.77	0.00	3.96	4.67	0.00
	GVW	3.1	5.8	7.7	32.6	17.2	43.5	61.7	28.1	75.2	103.3	0.0	84.1	97.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2019

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9