

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2019

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	19	989	669	15	589	46	15	36	111	41	1	1	12	0
	Flex	.00	.00	.00	2.63	.35	1.62	1.20	.76	3.40	2.72	1.35	.87	2.34	0.00
	Rigid	.00	.00	.00	3.51	.39	3.07	3.59	1.03	6.74	6.78	1.30	.99	5.94	0.00
	GVW	3.7	5.5	7.4	33.4	18.5	40.8	61.7	28.6	70.9	89.8	57.5	51.3	92.2	0.0
N	Num	7	477	315	9	319	19	4	21	46	21	0	1	5	0
	Flex	.00	.00	.00	2.81	.31	1.97	.98	.84	4.42	3.62	0.00	1.21	5.03	0.00
	Rigid	.00	.00	.00	3.79	.35	3.76	3.08	1.17	8.64	8.73	0.00	1.34	11.69	0.00
	GVW	3.3	5.9	7.7	33.5	19.0	41.7	58.1	30.0	76.7	88.8	0.0	55.6	113.2	0.0
S	Num	13	512	354	6	270	27	12	15	65	20	1	1	8	0
	Flex	.00	.00	.00	2.39	.44	1.64	1.24	.55	2.66	1.62	1.35	.27	.78	0.00
	Rigid	.00	.00	.00	3.24	.50	3.12	3.78	.70	5.35	4.36	1.30	.33	2.23	0.00
	GVW	3.9	5.1	7.1	34.0	17.9	40.9	64.8	25.7	66.7	89.9	57.5	42.3	74.9	0.0
N Lane1	Num	7	477	315	9	319	19	4	21	46	21	0	1	5	0
	Flex	.00	.00	.00	2.81	.31	1.97	.98	.84	4.42	3.62	0.00	1.21	5.03	0.00
	Rigid	.00	.00	.00	3.79	.35	3.76	3.08	1.17	8.64	8.73	0.00	1.34	11.69	0.00
	GVW	3.3	5.9	7.7	33.5	19.0	41.7	58.1	30.0	76.7	88.8	0.0	55.6	113.2	0.0
S Lane1	Num	13	512	354	6	270	27	12	15	65	20	1	1	8	0
	Flex	.00	.00	.00	2.39	.44	1.64	1.24	.55	2.66	1.62	1.35	.27	.78	0.00
	Rigid	.00	.00	.00	3.24	.50	3.12	3.78	.70	5.35	4.36	1.30	.33	2.23	0.00
	GVW	3.9	5.1	7.1	34.0	17.9	40.9	64.8	25.7	66.7	89.9	57.5	42.3	74.9	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2019

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9