

Idaho Transportation Department

Monthly WIM Distribution for Sep-2019

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	1,017	1,138	13	181	18	2	16	102	36	1	2	28	0
	Flex	.00	.00	.00	.57	.09	.29	.24	.25	.63	.55	.28	.42	.81	0.00
	Rigid	.00	.00	.00	.65	.09	.42	.88	.33	1.06	1.20	.26	.45	1.33	0.00
	GVW	1.2	3.6	6.2	22.8	16.1	25.5	44.6	24.0	46.6	62.5	44.0	49.0	64.1	0.0
N	Num	1	503	536	7	86	6	1	8	45	16	1	1	14	0
	Flex	.00	.00	.00	.61	.07	.32	.10	.33	.55	.72	.28	.13	.82	0.00
	Rigid	.00	.00	.00	.73	.08	.48	.40	.49	.91	1.47	.26	.15	1.29	0.00
	GVW	.9	3.7	6.2	22.6	16.1	25.7	35.3	25.2	43.9	58.6	44.0	41.1	63.1	0.0
S	Num	1	515	602	6	95	12	1	8	57	20	0	2	14	0
	Flex	.00	.00	.00	.55	.10	.29	.43	.16	.70	.39	0.00	.69	.68	0.00
	Rigid	.00	.00	.00	.61	.11	.42	1.60	.17	1.17	.94	0.00	.76	1.20	0.00
	GVW	1.3	3.6	6.2	23.0	16.1	25.7	55.7	21.7	48.6	64.6	0.0	58.2	61.6	0.0
N Lane1	Num	1	503	536	7	86	6	1	8	45	16	1	1	14	0
	Flex	.00	.00	.00	.61	.07	.32	.10	.33	.55	.72	.28	.13	.82	0.00
	Rigid	.00	.00	.00	.73	.08	.48	.40	.49	.91	1.47	.26	.15	1.29	0.00
	GVW	.9	3.7	6.2	22.6	16.1	25.7	35.3	25.2	43.9	58.6	44.0	41.1	63.1	0.0
S Lane1	Num	1	515	602	6	95	12	1	8	57	20	0	2	14	0
	Flex	.00	.00	.00	.55	.10	.29	.43	.16	.70	.39	0.00	.69	.68	0.00
	Rigid	.00	.00	.00	.61	.11	.42	1.60	.17	1.17	.94	0.00	.76	1.20	0.00
	GVW	1.3	3.6	6.2	23.0	16.1	25.7	55.7	21.7	48.6	64.6	0.0	58.2	61.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2019

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9