

Idaho Transportation Department

Monthly WIM Distribution for Oct-2019

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	891	1,112	12	242	17	2	17	98	43	2	1	25	0
	Flex	.00	.00	.00	.66	.08	.41	.58	.32	.69	.49	.21	.29	1.04	0.00
	Rigid	.00	.00	.00	.80	.08	.68	1.23	.46	1.18	1.11	.21	.33	1.78	0.00
	GVW	2.0	4.2	7.2	25.9	16.1	31.0	53.6	26.3	53.5	67.9	21.1	48.9	76.9	0.0
N	Num	1	450	546	6	115	6	1	8	43	20	1	1	13	0
	Flex	.00	.00	.00	.58	.07	.55	.61	.39	.53	.54	.04	1.00	1.22	0.00
	Rigid	.00	.00	.00	.69	.07	.93	1.39	.61	.88	1.14	.04	1.12	1.94	0.00
	GVW	2.6	4.2	7.3	24.9	16.0	32.8	56.0	27.3	49.0	62.3	18.5	60.0	77.3	0.0
S	Num	1	441	566	6	127	11	1	9	57	23	2	1	12	0
	Flex	.00	.00	.00	.66	.08	.32	.28	.21	.79	.44	.38	.24	.88	0.00
	Rigid	.00	.00	.00	.80	.09	.52	.78	.25	1.39	1.08	.38	.28	1.62	0.00
	GVW	2.0	4.2	7.1	25.7	16.3	29.8	49.9	24.8	56.4	72.6	23.7	48.8	75.8	0.0
N Lane1	Num	1	450	546	6	115	6	1	8	43	20	1	1	13	0
	Flex	.00	.00	.00	.58	.07	.55	.61	.39	.53	.54	.04	1.00	1.22	0.00
	Rigid	.00	.00	.00	.69	.07	.93	1.39	.61	.88	1.14	.04	1.12	1.94	0.00
	GVW	2.6	4.2	7.3	24.9	16.0	32.8	56.0	27.3	49.0	62.3	18.5	60.0	77.3	0.0
S Lane1	Num	1	441	566	6	127	11	1	9	57	23	2	1	12	0
	Flex	.00	.00	.00	.66	.08	.32	.28	.21	.79	.44	.38	.24	.88	0.00
	Rigid	.00	.00	.00	.80	.09	.52	.78	.25	1.39	1.08	.38	.28	1.62	0.00
	GVW	2.0	4.2	7.1	25.7	16.3	29.8	49.9	24.8	56.4	72.6	23.7	48.8	75.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2019

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9