

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2020

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	725	660	9	138	11	1	11	84	35	0	1	21	0
	Flex	.00	.00	.00	.68	.07	.65	.51	.32	.87	.66	0.00	.51	1.15	0.00
	Rigid	.00	.00	.00	.88	.07	1.15	1.19	.36	1.54	1.51	0.00	.58	2.07	0.00
	GVW	2.1	4.4	7.1	27.9	14.1	35.7	50.9	29.0	57.1	72.7	0.0	56.4	79.2	0.0
N	Num	1	368	316	5	69	7	1	6	35	17	0	1	10	0
	Flex	.00	.00	.00	.65	.06	.47	.31	.41	.82	.82	0.00	.59	1.07	0.00
	Rigid	.00	.00	.00	.80	.07	.79	.69	.45	1.43	1.76	0.00	.66	1.76	0.00
	GVW	2.1	4.5	7.2	27.0	14.3	33.9	40.2	31.4	55.5	69.9	0.0	55.5	73.5	0.0
S	Num	0	357	344	4	69	4	1	5	49	18	0	1	11	0
	Flex	0.00	.00	.00	.74	.08	.77	1.12	.28	.90	.52	0.00	.51	1.33	0.00
	Rigid	0.00	.00	.00	1.09	.08	1.38	2.69	.30	1.61	1.31	0.00	.59	2.50	0.00
	GVW	0.0	4.4	7.0	30.5	13.9	37.6	82.9	27.4	58.2	75.6	0.0	57.6	87.4	0.0
N Lane1	Num	1	368	316	5	69	7	1	6	35	17	0	1	10	0
	Flex	.00	.00	.00	.65	.06	.47	.31	.41	.82	.82	0.00	.59	1.07	0.00
	Rigid	.00	.00	.00	.80	.07	.79	.69	.45	1.43	1.76	0.00	.66	1.76	0.00
	GVW	2.1	4.5	7.2	27.0	14.3	33.9	40.2	31.4	55.5	69.9	0.0	55.5	73.5	0.0
S Lane1	Num	0	357	344	4	69	4	1	5	49	18	0	1	11	0
	Flex	0.00	.00	.00	.74	.08	.77	1.12	.28	.90	.52	0.00	.51	1.33	0.00
	Rigid	0.00	.00	.00	1.09	.08	1.38	2.69	.30	1.61	1.31	0.00	.59	2.50	0.00
	GVW	0.0	4.4	7.0	30.5	13.9	37.6	82.9	27.4	58.2	75.6	0.0	57.6	87.4	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2020

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9