

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2020

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	530	616	6	158	13	3	14	96	34	1	1	22	0
	Flex	.00	.00	.00	.74	.10	.74	1.14	.32	.86	.71	.20	.33	1.05	0.00
	Rigid	.00	.00	.00	.92	.11	1.37	2.83	.38	1.51	1.68	.20	.47	1.88	0.00
	GVW	1.9	4.3	7.1	26.4	15.8	35.0	67.2	27.1	54.9	71.9	32.0	48.1	75.3	0.0
N	Num	1	268	301	4	92	7	1	8	42	16	1	1	10	0
	Flex	.00	.00	.00	.86	.11	.70	1.11	.42	.96	.93	.36	.13	.91	0.00
	Rigid	.00	.00	.00	1.03	.12	1.25	2.85	.51	1.70	2.05	.37	.15	1.58	0.00
	GVW	1.2	4.4	7.4	27.5	16.2	35.8	66.4	29.2	57.3	70.7	43.7	43.8	69.9	0.0
S	Num	1	262	315	3	66	7	5	6	54	18	1	1	12	0
	Flex	.00	.00	.00	.65	.09	.72	.93	.20	.79	.52	.04	.47	1.14	0.00
	Rigid	.00	.00	.00	.82	.10	1.39	2.02	.21	1.40	1.34	.03	.69	2.08	0.00
	GVW	2.1	4.2	6.8	25.2	15.2	32.6	59.1	25.0	53.3	72.5	20.3	51.0	79.8	0.0
N Lane1	Num	1	268	301	4	92	7	1	8	42	16	1	1	10	0
	Flex	.00	.00	.00	.86	.11	.70	1.11	.42	.96	.93	.36	.13	.91	0.00
	Rigid	.00	.00	.00	1.03	.12	1.25	2.85	.51	1.70	2.05	.37	.15	1.58	0.00
	GVW	1.2	4.4	7.4	27.5	16.2	35.8	66.4	29.2	57.3	70.7	43.7	43.8	69.9	0.0
S Lane1	Num	1	262	315	3	66	7	5	6	54	18	1	1	12	0
	Flex	.00	.00	.00	.65	.09	.72	.93	.20	.79	.52	.04	.47	1.14	0.00
	Rigid	.00	.00	.00	.82	.10	1.39	2.02	.21	1.40	1.34	.03	.69	2.08	0.00
	GVW	2.1	4.2	6.8	25.2	15.2	32.6	59.1	25.0	53.3	72.5	20.3	51.0	79.8	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2020

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.7 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 5  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9