

Idaho Transportation Department

Monthly WIM Distribution for Jun-2022

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	16	1,609	1,175	7	71	61	9	108	78	42	1	3	15	0
	Flex	.08	.00	.01	.41	.72	.74	.39	.37	1.63	1.93	.45	1.31	1.75	0.00
	Rigid	.16	.00	.01	.57	.80	1.38	.87	.45	3.10	4.73	.99	2.64	3.35	0.00
	GVW	8.9	3.0	5.7	22.6	18.5	31.6	39.1	21.0	53.0	78.4	46.2	65.9	84.8	0.0
N	Num	13	811	575	5	35	22	5	60	37	19	1	2	8	0
	Flex	.03	.00	.03	.56	1.30	1.64	.69	.57	2.76	3.66	.45	2.05	2.22	0.00
	Rigid	.08	.01	.03	.72	1.49	3.13	1.42	.71	5.44	8.83	.99	4.02	4.17	0.00
	GVW	7.2	3.7	7.1	20.6	21.2	36.1	38.7	24.1	59.3	86.8	46.2	70.2	83.2	0.0
S	Num	3	798	600	2	35	39	5	48	40	23	0	2	7	0
	Flex	.22	.00	.00	.42	.20	.32	.35	.09	.60	.46	0.00	.62	1.03	0.00
	Rigid	.46	.00	.00	.63	.20	.57	.92	.11	.98	1.18	0.00	1.13	2.03	0.00
	GVW	16.5	2.3	4.3	31.0	16.2	29.7	47.9	17.1	47.7	68.7	0.0	57.8	83.4	0.0
N Lane1	Num	13	811	575	5	35	22	5	60	37	19	1	2	8	0
	Flex	.03	.00	.03	.56	1.30	1.64	.69	.57	2.76	3.66	.45	2.05	2.22	0.00
	Rigid	.08	.01	.03	.72	1.49	3.13	1.42	.71	5.44	8.83	.99	4.02	4.17	0.00
	GVW	7.2	3.7	7.1	20.6	21.2	36.1	38.7	24.1	59.3	86.8	46.2	70.2	83.2	0.0
S Lane1	Num	3	798	600	2	35	39	5	48	40	23	0	2	7	0
	Flex	.22	.00	.00	.42	.20	.32	.35	.09	.60	.46	0.00	.62	1.03	0.00
	Rigid	.46	.00	.00	.63	.20	.57	.92	.11	.98	1.18	0.00	1.13	2.03	0.00
	GVW	16.5	2.3	4.3	31.0	16.2	29.7	47.9	17.1	47.7	68.7	0.0	57.8	83.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2022

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9