

Idaho Transportation Department

Monthly WIM Distribution for Oct-2023

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 5
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,298	1,464	6	73	25	3	77	103	49	0	2	30	0
	Flex	.11	.00	.00	.62	.32	.38	.33	.13	.78	.75	0.00	.56	1.12	0.00
	Rigid	.23	.00	.00	.84	.32	.62	.82	.15	1.40	1.82	0.00	.81	2.06	0.00
	GVW	10.2	2.5	4.7	31.7	17.8	31.1	52.2	21.4	55.0	75.8	0.0	42.6	83.3	0.0
N	Num	2	646	730	3	37	10	2	40	45	23	0	1	15	0
	Flex	.19	.00	.00	.56	.28	.50	.23	.12	.66	.94	0.00	.21	1.03	0.00
	Rigid	.41	.00	.00	.77	.28	.82	.61	.14	1.13	2.22	0.00	.28	1.81	0.00
	GVW	7.9	2.6	4.7	31.9	17.3	32.1	52.1	21.4	51.2	75.8	0.0	42.3	76.5	0.0
S	Num	2	652	735	3	36	14	2	37	59	26	0	2	15	0
	Flex	.16	.00	.00	.66	.36	.31	.40	.15	.89	.58	0.00	.69	1.15	0.00
	Rigid	.34	.00	.00	.82	.37	.50	.89	.17	1.62	1.50	0.00	1.02	2.21	0.00
	GVW	14.6	2.4	4.7	30.0	18.3	30.9	50.3	21.5	58.0	75.9	0.0	45.6	89.2	0.0
N Lane1	Num	2	646	730	3	37	10	2	40	45	23	0	1	15	0
	Flex	.19	.00	.00	.56	.28	.50	.23	.12	.66	.94	0.00	.21	1.03	0.00
	Rigid	.41	.00	.00	.77	.28	.82	.61	.14	1.13	2.22	0.00	.28	1.81	0.00
	GVW	7.9	2.6	4.7	31.9	17.3	32.1	52.1	21.4	51.2	75.8	0.0	42.3	76.5	0.0
S Lane1	Num	2	652	735	3	36	14	2	37	59	26	0	2	15	0
	Flex	.16	.00	.00	.66	.36	.31	.40	.15	.89	.58	0.00	.69	1.15	0.00
	Rigid	.34	.00	.00	.82	.37	.50	.89	.17	1.62	1.50	0.00	1.02	2.21	0.00
	GVW	14.6	2.4	4.7	30.0	18.3	30.9	50.3	21.5	58.0	75.9	0.0	45.6	89.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2023

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 5
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9