

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2024

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 5  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	776	739	4	34	19	2	26	80	38	1	2	25	0
	Flex	.13	.00	.00	.45	.23	.35	.23	.17	.76	.57	.31	1.11	.89	0.00
	Rigid	.28	.00	.00	.60	.22	.62	.64	.20	1.37	1.37	.30	1.30	1.67	0.00
	GVW	15.9	2.5	4.2	30.3	16.6	32.2	46.9	25.0	58.7	72.7	30.9	63.7	84.9	0.0
N	Num	2	395	369	3	18	9	2	14	35	16	0	1	12	0
	Flex	.13	.00	.00	.47	.17	.30	.17	.16	.58	.56	0.00	1.06	.60	0.00
	Rigid	.28	.00	.00	.59	.17	.50	.50	.18	1.01	1.26	0.00	1.24	1.12	0.00
	GVW	15.0	2.5	4.1	30.2	15.5	30.7	45.6	24.9	54.6	68.4	0.0	61.8	72.2	0.0
S	Num	3	382	370	2	17	11	2	12	45	22	1	1	13	0
	Flex	.12	.00	.00	.54	.29	.40	.31	.18	.91	.57	.31	1.39	1.21	0.00
	Rigid	.26	.00	.00	.74	.29	.73	.79	.22	1.67	1.42	.30	1.71	2.26	0.00
	GVW	15.9	2.5	4.3	31.5	17.9	33.9	48.6	25.3	62.0	74.9	30.9	70.8	98.6	0.0
N Lane1	Num	2	395	369	3	18	9	2	14	35	16	0	1	12	0
	Flex	.13	.00	.00	.47	.17	.30	.17	.16	.58	.56	0.00	1.06	.60	0.00
	Rigid	.28	.00	.00	.59	.17	.50	.50	.18	1.01	1.26	0.00	1.24	1.12	0.00
	GVW	15.0	2.5	4.1	30.2	15.5	30.7	45.6	24.9	54.6	68.4	0.0	61.8	72.2	0.0
S Lane1	Num	3	382	370	2	17	11	2	12	45	22	1	1	13	0
	Flex	.12	.00	.00	.54	.29	.40	.31	.18	.91	.57	.31	1.39	1.21	0.00
	Rigid	.26	.00	.00	.74	.29	.73	.79	.22	1.67	1.42	.30	1.71	2.26	0.00
	GVW	15.9	2.5	4.3	31.5	17.9	33.9	48.6	25.3	62.0	74.9	30.9	70.8	98.6	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2024

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 5  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9