

Idaho Transportation Department

Monthly WIM Distribution for Feb-2024

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 5
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,017	882	4	40	14	1	35	102	53	0	2	23	0
	Flex	.08	.00	.00	.46	.23	.26	.37	.16	.73	.60	0.00	.50	.96	0.00
	Rigid	.16	.00	.00	.65	.23	.44	.75	.18	1.30	1.47	0.00	.62	1.85	0.00
	GVW	15.0	2.5	4.2	30.7	16.5	29.4	49.3	23.3	56.4	75.3	0.0	56.2	88.4	0.0
N	Num	1	506	441	3	21	7	1	18	49	18	0	1	11	0
	Flex	.24	.00	.00	.35	.18	.23	.61	.11	.47	.63	0.00	.47	.67	0.00
	Rigid	.51	.00	.00	.49	.17	.36	1.10	.13	.81	1.41	0.00	.61	1.20	0.00
	GVW	13.9	2.5	4.1	29.2	15.4	28.2	57.3	21.8	50.9	69.8	0.0	57.8	76.2	0.0
S	Num	2	511	441	2	19	7	1	17	53	35	0	1	12	0
	Flex	.07	.00	.00	.58	.29	.31	.19	.22	.95	.58	0.00	.62	1.22	0.00
	Rigid	.15	.00	.00	.81	.29	.54	.44	.25	1.73	1.49	0.00	.72	2.40	0.00
	GVW	15.6	2.4	4.2	32.7	17.6	30.9	41.5	25.0	61.2	77.6	0.0	58.5	99.5	0.0
N Lane1	Num	1	506	441	3	21	7	1	18	49	18	0	1	11	0
	Flex	.24	.00	.00	.35	.18	.23	.61	.11	.47	.63	0.00	.47	.67	0.00
	Rigid	.51	.00	.00	.49	.17	.36	1.10	.13	.81	1.41	0.00	.61	1.20	0.00
	GVW	13.9	2.5	4.1	29.2	15.4	28.2	57.3	21.8	50.9	69.8	0.0	57.8	76.2	0.0
S Lane1	Num	2	511	441	2	19	7	1	17	53	35	0	1	12	0
	Flex	.07	.00	.00	.58	.29	.31	.19	.22	.95	.58	0.00	.62	1.22	0.00
	Rigid	.15	.00	.00	.81	.29	.54	.44	.25	1.73	1.49	0.00	.72	2.40	0.00
	GVW	15.6	2.4	4.2	32.7	17.6	30.9	41.5	25.0	61.2	77.6	0.0	58.5	99.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2024

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 5
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9