

Idaho Transportation Department

Monthly WIM Distribution for May-2017

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	3,462	2,209	1	57	55	5	43	221	41	2	2	19	0
	Flex	.00	.00	.00	3.24	.45	.62	.39	.39	1.10	.87	.28	.15	.78	0.00
	Rigid	.00	.00	.00	3.94	.46	1.03	.53	.49	1.93	2.23	.29	.16	1.30	0.00
	GVW	1.5	3.4	4.2	28.0	18.6	30.9	27.6	24.1	56.0	79.2	24.9	32.4	61.2	0.0
N	Num	1	1,783	1,128	1	29	28	2	23	116	16	2	1	10	0
	Flex	.00	.00	.00	3.71	.41	.49	.49	.39	1.04	.78	.21	.17	.51	0.00
	Rigid	.00	.00	.00	4.46	.42	.82	.62	.49	1.75	1.78	.21	.18	.83	0.00
	GVW	1.5	3.5	4.2	27.0	18.6	29.1	27.3	24.0	55.9	71.2	24.6	39.7	55.2	0.0
S	Num	2	1,678	1,080	1	29	27	3	20	105	25	1	1	10	0
	Flex	.00	.00	.00	.27	.46	.78	.26	.40	1.19	.99	.50	.15	1.05	0.00
	Rigid	.00	.00	.00	.36	.48	1.27	.42	.51	2.14	2.68	.55	.17	1.74	0.00
	GVW	1.7	3.3	4.3	21.3	18.4	33.1	28.0	24.2	56.4	86.6	24.1	27.0	66.9	0.0
N Lane1	Num	1	1,783	1,128	1	29	28	2	23	116	16	2	1	10	0
	Flex	.00	.00	.00	3.71	.41	.49	.49	.39	1.04	.78	.21	.17	.51	0.00
	Rigid	.00	.00	.00	4.46	.42	.82	.62	.49	1.75	1.78	.21	.18	.83	0.00
	GVW	1.5	3.5	4.2	27.0	18.6	29.1	27.3	24.0	55.9	71.2	24.6	39.7	55.2	0.0
S Lane1	Num	2	1,678	1,080	1	29	27	3	20	105	25	1	1	10	0
	Flex	.00	.00	.00	.27	.46	.78	.26	.40	1.19	.99	.50	.15	1.05	0.00
	Rigid	.00	.00	.00	.36	.48	1.27	.42	.51	2.14	2.68	.55	.17	1.74	0.00
	GVW	1.7	3.3	4.3	21.3	18.4	33.1	28.0	24.2	56.4	86.6	24.1	27.0	66.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2017

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9