

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2018

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	3	1,458	1,835	2	69	121	6	39	302	43	3	2	35	0
	Flex	.00	.00	.00	.56	.39	.63	.63	.48	1.10	.65	.03	.13	.63	0.00
	Rigid	.00	.00	.00	.91	.40	1.14	.81	.69	1.95	1.49	.03	.13	.99	0.00
	GVW	2.7	3.1	4.0	26.1	17.9	30.8	32.0	26.5	58.0	65.9	19.8	37.4	58.0	0.0
N	Num	2	746	930	1	33	62	3	20	132	21	2	2	17	0
	Flex	.00	.00	.00	.70	.38	.64	.45	.58	1.09	.85	.02	.18	.55	0.00
	Rigid	.00	.00	.00	1.12	.39	1.16	.51	.93	1.87	1.93	.02	.19	.83	0.00
	GVW	2.5	3.0	3.8	27.9	17.2	30.9	26.1	29.1	53.1	66.4	18.7	43.0	53.7	0.0
S	Num	2	1,638	1,063	1	35	59	4	19	170	23	2	3	18	0
	Flex	.00	.00	.00	.18	.39	.62	.57	.38	1.11	.48	.05	.06	.69	0.00
	Rigid	.00	.00	.00	.31	.41	1.15	.77	.44	2.02	1.09	.06	.06	1.14	0.00
	GVW	3.0	3.4	4.4	26.2	18.5	31.1	33.4	24.1	61.8	66.0	22.8	29.5	61.8	0.0
N Lane1	Num	2	746	930	1	33	62	3	20	132	21	2	2	17	0
	Flex	.00	.00	.00	.70	.38	.64	.45	.58	1.09	.85	.02	.18	.55	0.00
	Rigid	.00	.00	.00	1.12	.39	1.16	.51	.93	1.87	1.93	.02	.19	.83	0.00
	GVW	2.5	3.0	3.8	27.9	17.2	30.9	26.1	29.1	53.1	66.4	18.7	43.0	53.7	0.0
S Lane1	Num	2	1,638	1,063	1	35	59	4	19	170	23	2	3	18	0
	Flex	.00	.00	.00	.18	.39	.62	.57	.38	1.11	.48	.05	.06	.69	0.00
	Rigid	.00	.00	.00	.31	.41	1.15	.77	.44	2.02	1.09	.06	.06	1.14	0.00
	GVW	3.0	3.4	4.4	26.2	18.5	31.1	33.4	24.1	61.8	66.0	22.8	29.5	61.8	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2018

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9