

Idaho Transportation Department

Monthly WIM Distribution for Jan-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	3	3,296	1,576	29	69	36	2	51	289	34	1	3	67	0
	Flex	.31	.00	.02	.10	.34	.36	.50	.27	1.11	.53	1.05	.92	1.17	0.00
	Rigid	.65	.00	.02	.12	.33	.63	1.39	.30	1.96	1.34	1.03	1.46	1.83	0.00
	GVW	21.3	5.6	9.5	8.6	19.4	32.2	62.2	27.3	65.0	76.2	54.4	68.5	79.0	0.0
N	Num	2	1,708	789	11	33	18	1	25	135	16	1	1	34	0
	Flex	.34	.00	.02	.12	.46	.42	.56	.39	1.24	.63	3.17	1.24	1.39	0.00
	Rigid	.71	.01	.02	.15	.45	.75	1.47	.43	2.18	1.56	3.17	1.43	2.39	0.00
	GVW	20.7	6.2	10.3	9.3	21.1	34.1	59.9	30.5	66.3	78.5	75.6	71.2	89.9	0.0
S	Num	2	1,588	787	17	36	19	2	26	154	18	1	2	34	0
	Flex	.17	.00	.01	.09	.24	.32	.47	.17	1.00	.42	.47	.81	.91	0.00
	Rigid	.36	.00	.01	.10	.23	.55	1.33	.17	1.76	1.05	.44	1.57	1.21	0.00
	GVW	21.5	4.9	8.7	8.0	18.0	31.1	61.7	24.1	63.8	71.9	48.8	67.7	67.0	0.0
N Lane1	Num	2	1,708	789	11	33	18	1	25	135	16	1	1	34	0
	Flex	.34	.00	.02	.12	.46	.42	.56	.39	1.24	.63	3.17	1.24	1.39	0.00
	Rigid	.71	.01	.02	.15	.45	.75	1.47	.43	2.18	1.56	3.17	1.43	2.39	0.00
	GVW	20.7	6.2	10.3	9.3	21.1	34.1	59.9	30.5	66.3	78.5	75.6	71.2	89.9	0.0
S Lane1	Num	2	1,588	787	17	36	19	2	26	154	18	1	2	34	0
	Flex	.17	.00	.01	.09	.24	.32	.47	.17	1.00	.42	.47	.81	.91	0.00
	Rigid	.36	.00	.01	.10	.23	.55	1.33	.17	1.76	1.05	.44	1.57	1.21	0.00
	GVW	21.5	4.9	8.7	8.0	18.0	31.1	61.7	24.1	63.8	71.9	48.8	67.7	67.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9