

Idaho Transportation Department

Monthly WIM Distribution for Feb-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	3,621	1,806	30	75	42	3	56	298	37	2	3	21	0
	Flex	.08	.00	.02	.07	.36	.38	.92	.36	1.08	.52	.74	.92	.96	0.00
	Rigid	.16	.00	.02	.08	.35	.63	2.43	.39	1.91	1.34	.71	1.32	1.42	0.00
	GVW	9.7	5.5	9.5	7.2	19.5	33.1	80.4	28.7	64.4	75.8	50.5	65.2	74.1	0.0
N	Num	2	1,838	909	14	38	21	2	27	141	19	2	2	11	0
	Flex	.00	.00	.02	.08	.41	.40	.89	.38	1.15	.56	.96	1.15	.75	0.00
	Rigid	.00	.00	.02	.08	.40	.67	2.38	.42	2.03	1.44	.91	1.50	1.17	0.00
	GVW	3.8	5.8	9.9	7.2	20.5	33.3	77.8	30.0	65.5	75.8	55.0	69.1	71.3	0.0
S	Num	2	1,783	897	16	37	21	2	29	157	19	2	2	11	0
	Flex	.09	.00	.01	.06	.31	.36	.77	.33	1.02	.48	.68	.79	1.12	0.00
	Rigid	.18	.00	.01	.06	.30	.61	2.06	.37	1.80	1.21	.65	1.28	1.59	0.00
	GVW	10.4	5.2	9.1	6.9	18.8	32.9	75.8	27.7	63.6	75.4	48.6	63.8	75.9	0.0
N Lane1	Num	2	1,838	909	14	38	21	2	27	141	19	2	2	11	0
	Flex	.00	.00	.02	.08	.41	.40	.89	.38	1.15	.56	.96	1.15	.75	0.00
	Rigid	.00	.00	.02	.08	.40	.67	2.38	.42	2.03	1.44	.91	1.50	1.17	0.00
	GVW	3.8	5.8	9.9	7.2	20.5	33.3	77.8	30.0	65.5	75.8	55.0	69.1	71.3	0.0
S Lane1	Num	2	1,783	897	16	37	21	2	29	157	19	2	2	11	0
	Flex	.09	.00	.01	.06	.31	.36	.77	.33	1.02	.48	.68	.79	1.12	0.00
	Rigid	.18	.00	.01	.06	.30	.61	2.06	.37	1.80	1.21	.65	1.28	1.59	0.00
	GVW	10.4	5.2	9.1	6.9	18.8	32.9	75.8	27.7	63.6	75.4	48.6	63.8	75.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9