

Idaho Transportation Department

Monthly WIM Distribution for Mar-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	3,513	1,951	15	71	53	7	78	323	79	4	3	21	0
	Flex	.28	.00	.02	.13	.40	.39	.91	.35	1.18	.61	1.07	.80	1.20	0.00
	Rigid	.57	.00	.02	.17	.39	.65	2.33	.39	2.07	1.53	1.04	1.35	1.84	0.00
	GVW	19.9	5.6	9.8	14.9	19.9	33.2	79.3	27.8	65.0	75.9	53.2	66.7	78.2	0.0
N	Num	2	1,697	965	8	31	24	6	41	168	38	2	3	10	0
	Flex	.17	.00	.02	.17	.24	.37	.64	.37	1.00	.39	.60	.70	1.25	0.00
	Rigid	.29	.00	.02	.25	.24	.64	1.69	.43	1.80	.91	.58	1.40	1.87	0.00
	GVW	16.9	5.0	9.0	19.4	17.5	32.6	72.7	26.6	62.4	63.2	45.6	65.3	76.7	0.0
S	Num	1	1,815	986	7	40	29	3	38	155	41	2	1	11	0
	Flex	.43	.00	.03	.06	.51	.41	1.21	.32	1.36	.80	1.59	1.05	1.13	0.00
	Rigid	.90	.00	.02	.09	.51	.67	3.02	.36	2.35	2.04	1.54	1.22	1.77	0.00
	GVW	25.3	6.1	10.6	9.4	21.7	33.8	87.1	29.2	67.6	86.4	61.4	69.9	79.0	0.0
N Lane1	Num	2	1,697	965	8	31	24	6	41	168	38	2	3	10	0
	Flex	.17	.00	.02	.17	.24	.37	.64	.37	1.00	.39	.60	.70	1.25	0.00
	Rigid	.29	.00	.02	.25	.24	.64	1.69	.43	1.80	.91	.58	1.40	1.87	0.00
	GVW	16.9	5.0	9.0	19.4	17.5	32.6	72.7	26.6	62.4	63.2	45.6	65.3	76.7	0.0
S Lane1	Num	1	1,815	986	7	40	29	3	38	155	41	2	1	11	0
	Flex	.43	.00	.03	.06	.51	.41	1.21	.32	1.36	.80	1.59	1.05	1.13	0.00
	Rigid	.90	.00	.02	.09	.51	.67	3.02	.36	2.35	2.04	1.54	1.22	1.77	0.00
	GVW	25.3	6.1	10.6	9.4	21.7	33.8	87.1	29.2	67.6	86.4	61.4	69.9	79.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9