

Idaho Transportation Department

Monthly WIM Distribution for Apr-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	3	3,815	2,134	11	90	52	10	89	325	52	3	4	22	0
	Flex	.22	.00	.02	.24	.42	.51	.65	.34	1.29	.65	.76	1.02	1.55	0.00
	Rigid	.53	.00	.02	.31	.42	.86	1.79	.39	2.31	1.65	.73	1.71	2.16	0.00
	GVW	16.7	5.6	10.1	13.1	20.2	35.3	67.3	27.6	66.4	78.6	49.1	70.0	79.3	0.0
N	Num	3	1,844	1,050	4	43	24	7	46	171	23	2	3	11	0
	Flex	.15	.00	.02	.37	.32	.50	.62	.33	1.19	.63	.30	.97	1.96	0.00
	Rigid	.31	.00	.02	.48	.31	.84	1.70	.39	2.17	1.60	.28	1.97	2.57	0.00
	GVW	10.9	5.1	9.4	17.0	18.6	34.3	67.8	26.4	65.1	78.1	43.0	70.8	77.7	0.0
S	Num	2	1,972	1,084	7	47	28	3	43	154	29	1	1	12	0
	Flex	.26	.00	.03	.17	.52	.51	.63	.35	1.41	.68	2.00	1.26	1.09	0.00
	Rigid	.64	.00	.03	.21	.51	.85	1.71	.38	2.47	1.73	1.95	1.72	1.68	0.00
	GVW	20.1	6.1	10.8	10.4	21.6	35.9	59.7	28.8	67.8	79.4	64.9	74.5	79.4	0.0
N Lane1	Num	3	1,844	1,050	4	43	24	7	46	171	23	2	3	11	0
	Flex	.15	.00	.02	.37	.32	.50	.62	.33	1.19	.63	.30	.97	1.96	0.00
	Rigid	.31	.00	.02	.48	.31	.84	1.70	.39	2.17	1.60	.28	1.97	2.57	0.00
	GVW	10.9	5.1	9.4	17.0	18.6	34.3	67.8	26.4	65.1	78.1	43.0	70.8	77.7	0.0
S Lane1	Num	2	1,972	1,084	7	47	28	3	43	154	29	1	1	12	0
	Flex	.26	.00	.03	.17	.52	.51	.63	.35	1.41	.68	2.00	1.26	1.09	0.00
	Rigid	.64	.00	.03	.21	.51	.85	1.71	.38	2.47	1.73	1.95	1.72	1.68	0.00
	GVW	20.1	6.1	10.8	10.4	21.6	35.9	59.7	28.8	67.8	79.4	64.9	74.5	79.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9