

Idaho Transportation Department

Monthly WIM Distribution for May-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	6	3,820	2,162	8	87	58	9	87	302	52	2	4	17	0
	Flex	.07	.00	.02	.48	.41	.43	.54	.25	1.24	.69	1.39	1.03	1.17	0.00
	Rigid	.13	.00	.02	.68	.41	.73	1.39	.28	2.23	1.76	2.24	1.78	1.82	0.00
	GVW	7.3	5.5	9.9	23.8	19.9	33.4	59.9	24.9	65.2	79.0	62.9	70.1	76.3	0.0
N	Num	5	1,859	1,069	3	43	27	7	44	160	25	2	3	8	0
	Flex	.03	.00	.02	.65	.31	.38	.52	.21	1.10	.52	1.14	.89	.95	0.00
	Rigid	.04	.00	.02	.86	.30	.65	1.38	.22	2.00	1.39	2.57	1.75	1.46	0.00
	GVW	5.1	4.9	9.1	31.5	18.4	32.2	60.9	23.3	62.3	74.2	62.8	68.5	65.9	0.0
S	Num	2	1,961	1,094	5	43	31	3	42	142	27	1	2	8	0
	Flex	.29	.00	.03	.33	.51	.48	.58	.30	1.39	.86	2.33	1.15	1.39	0.00
	Rigid	.61	.00	.03	.48	.51	.82	1.43	.33	2.49	2.12	2.34	1.54	2.18	0.00
	GVW	18.8	6.0	10.7	18.2	21.3	34.8	55.4	26.6	68.2	83.7	67.0	67.2	86.5	0.0
N Lane1	Num	5	1,859	1,069	3	43	27	7	44	160	25	2	3	8	0
	Flex	.03	.00	.02	.65	.31	.38	.52	.21	1.10	.52	1.14	.89	.95	0.00
	Rigid	.04	.00	.02	.86	.30	.65	1.38	.22	2.00	1.39	2.57	1.75	1.46	0.00
	GVW	5.1	4.9	9.1	31.5	18.4	32.2	60.9	23.3	62.3	74.2	62.8	68.5	65.9	0.0
S Lane1	Num	2	1,961	1,094	5	43	31	3	42	142	27	1	2	8	0
	Flex	.29	.00	.03	.33	.51	.48	.58	.30	1.39	.86	2.33	1.15	1.39	0.00
	Rigid	.61	.00	.03	.48	.51	.82	1.43	.33	2.49	2.12	2.34	1.54	2.18	0.00
	GVW	18.8	6.0	10.7	18.2	21.3	34.8	55.4	26.6	68.2	83.7	67.0	67.2	86.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9