

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2019

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	10	3,891	2,187	7	79	51	3	82	285	48	2	5	23	0
	Flex	.07	.00	.02	.53	.43	.50	.99	.27	1.23	.69	1.78	.89	1.35	0.00
	Rigid	.13	.00	.02	.69	.42	.87	2.67	.30	2.21	1.73	2.42	1.52	2.03	0.00
	GVW	5.9	5.5	9.8	22.6	19.9	34.1	77.5	25.0	64.4	78.6	64.1	64.9	73.8	0.0
N	Num	9	1,882	1,080	2	38	24	3	41	152	23	1	4	11	0
	Flex	.02	.00	.02	.73	.35	.52	1.15	.23	1.08	.62	.89	.94	.93	0.00
	Rigid	.04	.00	.02	.95	.35	.92	3.13	.25	1.97	1.60	1.89	1.79	1.45	0.00
	GVW	3.5	5.0	9.0	31.8	18.6	33.8	83.1	23.6	61.5	77.8	58.5	65.7	59.3	0.0
S	Num	2	2,009	1,107	5	41	27	1	41	134	25	1	2	12	0
	Flex	.12	.00	.03	.46	.49	.47	.74	.31	1.40	.78	3.48	.81	1.73	0.00
	Rigid	.24	.00	.03	.60	.49	.79	1.93	.34	2.49	1.89	3.52	1.08	2.56	0.00
	GVW	9.7	6.0	10.6	20.5	21.0	34.4	68.1	26.4	67.6	80.0	75.8	64.8	87.0	0.0
N Lane1	Num	9	1,882	1,080	2	38	24	3	41	152	23	1	4	11	0
	Flex	.02	.00	.02	.73	.35	.52	1.15	.23	1.08	.62	.89	.94	.93	0.00
	Rigid	.04	.00	.02	.95	.35	.92	3.13	.25	1.97	1.60	1.89	1.79	1.45	0.00
	GVW	3.5	5.0	9.0	31.8	18.6	33.8	83.1	23.6	61.5	77.8	58.5	65.7	59.3	0.0
S Lane1	Num	2	2,009	1,107	5	41	27	1	41	134	25	1	2	12	0
	Flex	.12	.00	.03	.46	.49	.47	.74	.31	1.40	.78	3.48	.81	1.73	0.00
	Rigid	.24	.00	.03	.60	.49	.79	1.93	.34	2.49	1.89	3.52	1.08	2.56	0.00
	GVW	9.7	6.0	10.6	20.5	21.0	34.4	68.1	26.4	67.6	80.0	75.8	64.8	87.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2019

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9